ELECTRICITY GENERATED BY WASTE MATERIAL

SONARGAON UNIVERSITY (SU)

Supervised By:

Shithi Dev
Lecturer
Faculty of Engineering
Department Electrical and Electronics Engineering

Submitted By

Abu Bakar Siddiq	ID: EEE2102023047
Md. Rajib Ahmed	ID: EEE2102023082
Manjurul Islam	ID: EEE2102023096
Md. Shihab Saruar	ID: EEE2102023074
Md. Rashed	ID: EEE2102023069

Sonargaon University (SU)
147/1, Panthapath,
Dhaka-1215, Bangladesh

Date of Submission: January, 2025

DECLERATION

This is to certify that the project titled "**Electricity Generated By Waste Material**" is the result of our study in partial fulfillment of the B.Sc. Engineering degree under the supervision of Shithi Dev, Lecturer, Department of Electrical and Electronic Engineering (EEE), Sonargaon University, Bangladesh, It is also hereby declared the this project or any part of it is not been submitted elsewhere for the award of any degree.

Signature of the Canditates

.....	.....
Abu Bakar Siddiq	Manjurul Islam
.....	.....
Md. Shihab Saruar	Md. Rajib Ahmed
.....	
Md. Rashed	

Certificate of Approval

The project titled **"Electricity Generated By Waste Material"** submitted By **Abu Bakar Siddiq** (ID: EEE2102023047), **Manjurul Islam** (ID: EEE2102023096), **Md. Rajib Ahmed** (ID: EEE2102023082**), Md. Shihab Saruar** (ID: EEE2102023074), **Md. Rashed** (ID: EEE2102023069) has been accepted as satisfactory in partial fulfillment of the requirement for the degree of Bachelor of Science in Electrical and Electronic Engineering on January 2025.

Supervisor

……..

Shithi Dev
Lecturer
Faculty of Engineering
Department Electrical and Electronics Engineering (EEE)
Sonargaon University, Bangladesh

ACKNOWLEDGEMENT

First of all, we are grateful to Allah, the almighty for giving us the courage and enthusiasm to complete the thesis work. The authors express their gratitude to “Shithi Dev” for his constant & meticulous supervision, valuable suggestion and encouragement to carry out this work. For all this, the authors acknowledge their sincere gratitude to him. We are also grateful to all our thesis & project working team of SU for their help in construction of the project work and give their valuable knowledge and time for completing the experiment. Finally, we would like to thank everybody who supported us in any respect for the completion of the thesis.

ABSTRACT

The Purpose of Making this Project is to generate electric energy from waste Materials such a plastic, rubber, waste and waste etc. and to convert that less electricity energy into more high power electricity energy by electric coil , this process is called boosting Process. Normally waste is any undesirable substances which has been obtained as an outcome of all those Humans and Animals activities. Which includes rotten food stuffs, treated biomedical solid wastes etc. This is basically an advanced process where cost of generation of electricity is also been saved as we didn't need to use fossil It also includes all those waste materials which is been collected by Municipals Corporation also fuel, coal, or any other raw materials which costs high and it also produces less harmful gases as compare to other methods of generation.

TABLE OF CONTENTS

Name of the Contents		Page No.
APPROVAL		II
DECLERATION		III
ACKNOWLEDGEMENT		IV
ABSTRACT		VI
TABLE OF CONTENTS		VI
LIST OF FIGURES		VII
LIST OF TABLES		VIII

Chapter 1: Introduction

1.1	General	01
1.2	Objective of the Project	01
1.3	Background of the Project	02
1.4	Earlier Research	02
1.5	Brief Overview of The Project	04
1.6	Motivation for Project	04
1.7	Project Management	06

Chapter 2: Theoretical Review

2.1	Introduction	10
2.2	Solid Waste	10
2.3	Thermo Electric Plant	15
2.4	Literature Survey	16

Chapter 3: Methodology

3.1	Process of Project	17
3.2	Block Diagram of This Project	19
3.3	Circuit Diagram of This Project	20
3.4	Working Principal	20
3.5	The list of Devices used in the Project is Given Below	21
3.6	Node MCU	21
3.6.1	Technical Specifications	21
3.7	Buck Module	22
3.8	Battery	22
3.8.1	Specifications	23
3.9	LCD Display	23
3.10	Voltage Sensor	24
3.10.1	Features	24
3.11	Paltier Module	25
3.11.1	Specifications	25

Chapter 4: Result and Discussion

4.1	Result	26
4.2	Result Analysis	27
4.3	Discussion	28

Chapter 5: Conclusion

5.1	Advantage	29
5.2	Application	29
5.3	Future Scope	30
5.4	Conclusion	30

References 31

LIST OF FIGURES

Figure No	Figure Contains	Page No
Figure 1.3	Project Management	08
Figure 2.1	Rate of Growth of World Population	13
Figure 2.2	Projected Waste Generation by Region	13
Figure 2.3	Global Waste Composition	15
Figure 2.4	Plants Design	16
Figure 3.1	Project Setup	19
Figure 3.2	Block Diagram	19
Figure 3.3	Circuit Diagram	20
Figure 3.4	Node MCU	21
Figure 3.5	LM2596 Voltage Converter	22
Figure 3.6	Battery	22
Figure 3.7	LCD Display	23
Figure 3.8	DC Voltage Sensor	24
Figure 3.9	Paltier Module	25

LIST OF TABLES

Table No	Table Contains	Page No
Table- 01	LCD Display Outline	23
Table- 02	Electricity Generation Performance- 01	27
Table- 03	Electricity Generation Performance- 02	27

Chapter 1 Introduction

1.1 General

The Purpose of Making this Project is to generate electric energy from waste Materials such a plastic, rubber, waste and waste etc. and to convert that less electricity energy into more high power electricity energy. Normally waste is any undesirable substances which has been obtained as a outcome of all those Humans and Animals activities. which includes rotten food stuffs, treated biomedical solid wastes etc. This is basically an advanced process where cost of generation of electricity is also been saved as we didn't need to use fossil It also includes all those waste materials which is been collected by Municipals Corporation also fuel, coal, or any other raw materials which costs high and it also produces less harmful gases as compare to other methods of generation. The large amount of waste can generate a large amount of heat energy by burning it in a controlled manor. In this Process we generate electricity by burning waste that is collected from the door to door, mostly house wastes. The main components used in this methods are heating panels, boosting coils, diodes, LEDs, capacitors, resistors, battery, PCB board etc. The demand of Electricity is increasing day by day, thus it is necessary to find out the different types of source which can be used as the input in production of the electricity especially for developing countries like Bangladesh. This method is one of the best methods to generate electricity. The greatest advantage of this project is that it does not require any other fuel except waste.

1.2 Objective of the Project

The objective of generating electricity from trash or waste (commonly referred to as Waste-to-Energy or WtE) is to convert municipal solid waste, agricultural residues, industrial waste, or other types of non-recyclable materials into usable electrical energy. Here are the main objectives of such a project:

- Sustainable Waste Management: To provide an alternative method of managing waste by reducing the volume of trash sent to landfills and promoting environmentally friendly disposal methods.
- Energy Recovery: To recover valuable energy content from waste materials and convert it into electricity, reducing dependence on traditional fossil fuels and enhancing energy security.
- Reduction of Greenhouse Gas Emissions: By diverting waste from landfills, which produce methane (a potent greenhouse gas), and using it to generate electricity, WtE projects aim to reduce overall greenhouse gas emissions.
- Resource Optimization: To make efficient use of the energy potential contained in waste materials, contributing to a circular economy where waste is viewed as a valuable resource.

1.3 Background of the Project

The gigantic growth in the amount of waste materials produced in Bangladesh and their potentially dangerous results in the environment and human health Which have led to create several disease in Human bodies, So we need to ingurgitate scholarly methods for safe arrangement of garbage. This is an innovative idea of generating electricity Using solid waste. Which lead to decrease pollution by stoping to produce almost all dangerous gasses like CO2,CO, SO2,NO2 and Heavy metals such as mercury to a huge number. With a population of millions India produces large number of waste every day to Contemplate about this idea. So, we felt that it is valuable working on this project and it is high time to inject the idea of Waste to Energy in
Bangladesh. Firstly, a map plan was carried out for research to collect the fact of total waste generation in Bangladesh. During this research it was found that some locals were generating electricity using this process ago which encouraged the researchers to carry forward this Project.

1.4 Earlier Research

The concept of generating electricity from trash or waste, known as Waste-to-Energy (WtE), has a history dating back several decades. Here is an overview of earlier research and development in this field:
1. Early Incineration Plants (19th and 20th Centuries)
1880s: The idea of waste incineration began in the late 19th century, with the first incineration plant (often called a "destructor") built in Nottingham, England, in 1874. These early plants focused primarily on waste reduction rather than energy generation.
1920s-1950s: The development of incinerators continued throughout the early 20th century, especially in Europe and the United States. Initially, these plants did not aim to recover energy. However, by the mid-20th century, some incinerators began to capture heat for district heating.
2. Introduction of Waste-to-Energy (1950s-1970s)
1950s: Research and development into Waste-to-Energy began in earnest, particularly in Europe. Sweden, Denmark, and Germany were among the pioneers in converting waste into energy, using the heat generated from incineration to produce steam and electricity.
1960s-1970s: The oil crises of the 1970s spurred greater interest in alternative energy sources, including waste-to-energy technologies. Researchers began to explore more efficient combustion methods, pollution control measures, and energy recovery techniques. The first modern Waste-to-Energy plants were developed, combining waste incineration with energy recovery, such as generating electricity or producing steam for heating.
3. Advancements in Combustion Technologies and Pollution Control (1980s-1990s)
1980s: Research focused on improving combustion efficiency and reducing harmful emissions. The introduction of advanced air pollution control systems, such as electrostatic precipitators and scrubbers, helped to mitigate the release of dioxins, furans, and other pollutants.
1990s: The development of alternative technologies, such as gasification and pyrolysis, gained traction. These processes convert waste into syngas (a mixture of hydrogen and carbon

monoxide), which can be used to generate electricity or as a feedstock for producing chemicals and fuels. Research also explored anaerobic digestion to convert organic waste into biogas for energy production.

4. Shift to Sustainable Waste Management (2000s-2010s)

2000s: Research increasingly focused on integrating Waste-to-Energy into broader waste management strategies, emphasizing recycling and the circular economy. Studies investigated combining WtE with recycling, composting, and material recovery facilities to maximize resource utilization.

2010s: Innovations in waste sorting, preprocessing, and conversion technologies, such as plasma gasification, aimed at enhancing the efficiency and environmental performance of WtE facilities. Researchers also explored Life Cycle Assessment (LCA) to evaluate the overall environmental impact of Waste-to-Energy processes, accounting for factors like greenhouse gas emissions and resource consumption.

5. Emerging Technologies and Circular Economy Focus (2020s-Present)

2020s: Recent research has emphasized improving the efficiency and sustainability of WtE processes by using artificial intelligence (AI) and machine learning to optimize plant operations, increase energy recovery rates, and minimize environmental impact. Studies have focused on carbon capture and storage (CCS) technologies to mitigate CO2 emissions from Waste-to-Energy plants.

Researchers are also exploring decentralized and small-scale Waste-to-Energy systems, particularly in developing countries, to address local waste management challenges and provide a sustainable energy source.

6. Key Research Areas

Feedstock Optimization: Research into the best types of waste for energy production, including mixed municipal solid waste (MSW), agricultural residues, and industrial waste.

Advanced Conversion Technologies: Continued innovation in gasification, pyrolysis, and anaerobic digestion processes.

Emission Reduction and Environmental Impact: Ongoing studies on reducing emissions of pollutants, including carbon dioxide, heavy metals, and particulate matter, as well as developing more efficient scrubbing and filtering systems.

Integration with Renewable Energy: Exploring the integration of Waste-to-Energy with other renewable energy sources (like solar and wind) for a more stable and reliable power supply.

7. International Collaboration and Policy Development

Various international collaborations and research initiatives, such as those sponsored by the European Union, the United Nations, and national governments, have driven advancements in Waste-to-Energy technology and practices.

Research continues to explore regulatory frameworks and public policies to promote the adoption of Waste-to-Energy solutions worldwide while addressing social acceptance and environmental concerns.

1.5 Brief Overview of the Project

The Waste-to-Energy (WtE) project aims to convert waste materials, such as municipal solid waste (MSW), agricultural residues, industrial waste, and other non-recyclable materials, into usable electricity. This project focuses on utilizing waste as a valuable resource for energy production while minimizing environmental impacts and enhancing waste management practices.

Key Components of the Project:

Collection and Sorting of Waste: Waste is collected from various sources, such as households, industries, and agricultural activities, and sorted to separate recyclable and non-recyclable materials. Only non-recyclable, combustible waste is used for energy generation.

Waste Conversion Technologies:

Incineration: The most common WtE method involves burning waste at high temperatures to produce heat, which is used to generate steam and drive turbines for electricity production.

Gasification and Pyrolysis: Advanced thermal technologies that convert waste into syngas (a mixture of hydrogen and carbon monoxide) through partial combustion (gasification) or heating without oxygen (pyrolysis). The syngas can be burned to produce electricity.

Anaerobic Digestion: A biological process that breaks down organic waste (like food waste and agricultural residues) in the absence of oxygen, producing biogas, which can be used to generate electricity.

Energy Generation and Distribution: The electricity generated from the converted waste is fed into the power grid, providing a renewable and sustainable source of energy for households, businesses, and industries.

Environmental and Emission Controls: Advanced technologies are implemented to control emissions of pollutants (such as dioxins, furans, and particulate matter) and to ensure compliance with environmental standards. This includes the use of scrubbers, filters, and carbon capture technologies.

Resource Recovery and Byproducts: In addition to electricity, Waste-to-Energy processes can recover valuable byproducts like metals, ash, and biochar, which can be reused in construction, agriculture, or other applications.

1.7 Motivation for Project

The motivation behind generating electricity from trash or waste, commonly known as the Waste-to-Energy (WtE) project, is driven by a combination of environmental, economic, social, and energy-related factors. This approach provides a sustainable solution to the growing waste management challenge while contributing to energy production and reducing environmental impacts.

Here are the key motivations for undertaking a Waste-to-Energy project:

1. Sustainable Waste Management

Reducing Landfill Dependency: Traditional waste disposal methods, such as landfilling, occupy large areas of land, contaminate soil and water, and emit significant amounts of methane, a potent greenhouse gas. Waste-to-Energy projects provide an alternative method for disposing of waste, reducing the volume of waste sent to landfills by up to 90%.

Managing Increasing Waste Volumes: As urbanization, population growth, and consumption patterns increase, the amount of waste generated continues to rise. WtE projects offer a way to manage this growing volume of waste sustainably, converting it into a valuable resource.

2. Energy Security and Diversification

Renewable Energy Source: Waste is a continuous and locally available resource, making it a reliable and renewable energy source. Generating electricity from waste reduces reliance on traditional fossil fuels (like coal, oil, and natural gas), enhancing energy security.

Stable Energy Supply: Unlike other renewable energy sources, such as wind and solar, Waste-to-Energy plants can provide a constant and predictable energy supply, helping to balance the grid and provide base-load power.

3. Reduction of Greenhouse Gas Emissions

Lower Emissions than Landfills: Waste-to-Energy projects help mitigate greenhouse gas emissions by diverting organic waste from landfills, where it would decompose anaerobically and release methane, a greenhouse gas 25 times more potent than CO2 over a 100-year period.

Reduced Carbon Footprint: By displacing energy generated from fossil fuels and reducing methane emissions, WtE contributes to a lower carbon footprint and helps meet climate goals and international agreements, such as the Paris Agreement.

4. Economic Benefits and Job Creation

Generation of Revenue: Waste-to-Energy plants generate electricity, which can be sold to the grid or used locally, creating a new revenue stream for municipalities and businesses. Additionally, recovered materials (like metals) can be sold for recycling.

Local Job Creation: WtE projects create jobs in plant construction, operation, and maintenance, as well as in waste collection, sorting, and transportation. This supports local economies and contributes to economic development.

Cost Savings in Waste Management: By reducing the volume of waste that requires landfilling, municipalities can save on waste transportation and landfill maintenance costs.

5. Public Health and Environmental Protection

Improved Public Health: Reducing the amount of waste sent to landfills decreases the risk of groundwater contamination, pest infestations, and harmful gas emissions, thereby improving public health and quality of life in surrounding communities.

Minimizing Pollution: Modern WtE plants are equipped with advanced pollution control technologies that minimize the release of harmful emissions like dioxins, furans, and particulate matter, reducing the overall environmental footprint of waste disposal.

6. Resource Optimization and Circular Economy

Maximizing Resource Use: WtE projects align with the principles of a circular economy by treating waste as a valuable resource. They help recover energy and materials from waste, ensuring that resources are utilized efficiently and repeatedly.

Support for Recycling and Reuse: By focusing on non-recyclable waste, Waste-to-Energy complements recycling efforts, helping to recover metals, minerals, and other valuable materials that can be reused in various industries.

7. Technological Advancement and Innovation

Promoting Innovation: The development of WtE projects encourages technological innovation in areas such as waste sorting, advanced combustion, gasification, pyrolysis, and pollution control. This drives further advancements in clean energy technology and sustainable practices.

Encouraging Investment in Clean Technologies: Governments and private sectors are motivated to invest in innovative Waste-to-Energy technologies, driving further research and development and helping to achieve a low-carbon economy.

8. Policy and Regulatory Drivers

Compliance with Environmental Regulations: Many countries have stringent waste management and emissions regulations that encourage or mandate the use of WtE technologies to reduce the environmental impact of waste disposal.

Support for Renewable Energy Targets: Waste-to-Energy projects contribute to meeting national and international renewable energy targets and commitments, fostering a shift towards more sustainable energy systems.

9. Community and Social Benefits

Raising Environmental Awareness: WtE projects can help educate the public about the importance of proper waste management, recycling, and reducing waste generation, promoting more sustainable lifestyles.

Enhancing Community Resilience: By providing a local source of renewable energy and reducing dependency on external energy sources, Waste-to-Energy projects can increase the resilience of communities to energy supply disruptions.

1.8 Project Management

Effective project management is crucial for the successful planning, execution, and operation of a Waste-to-Energy (WtE) project. The management process involves organizing resources, coordinating tasks, and managing stakeholders to ensure that the project is completed on time, within budget, and according to the required quality standards.

Key Components of Project Management:

Project Initiation

Feasibility Study: Conduct a comprehensive feasibility study to assess the technical, economic, and environmental viability of the Waste-to-Energy project. This includes analyzing waste availability, technology options, regulatory requirements, site location, and potential environmental and social impacts.

Stakeholder Analysis: Identify and engage key stakeholders (government authorities, community groups, investors, waste suppliers, technology providers, etc.) to understand their interests, concerns, and expectations.

Project Objectives and Scope: Define clear project objectives, scope, deliverables, and expected outcomes, including the amount of electricity to be generated, waste volume to be processed, and emission reduction targets.

Project Planning

Develop a Project Plan: Create a detailed project plan outlining all activities, tasks, timelines, resources, and responsibilities. The plan should cover all phases of the project, from design and construction to operation and maintenance.

Budget and Funding: Prepare a comprehensive budget that includes capital expenditures (CAPEX), operating expenses (OPEX), and maintenance costs. Identify potential sources of funding, such as government grants, loans, private investments, or public-private partnerships (PPP).

Risk Assessment and Mitigation: Conduct a risk assessment to identify potential risks (technical, financial, environmental, social, etc.) and develop a risk management plan to mitigate these risks. Include contingency plans for unforeseen circumstances.

Regulatory Compliance and Permitting: Ensure compliance with all relevant local, national, and international regulations, including environmental permits, waste management licenses, construction approvals, and emissions standards. Obtain necessary permits from authorities.

Project Design and Engineering

Technology Selection: Choose the most suitable technology for waste conversion based on waste characteristics, project size, environmental impact, and energy output requirements (e.g., incineration, gasification, pyrolysis, anaerobic digestion).

Site Selection and Design: Select an appropriate site for the WtE plant considering factors such as proximity to waste sources, grid connectivity, environmental impact, community acceptance, and logistics. Develop a detailed site layout and design plan, including plant infrastructure, equipment, and utilities.

Detailed Engineering: Develop detailed engineering designs for all aspects of the WtE plant, including waste processing facilities, energy conversion systems, emission control equipment, and auxiliary systems.

Procurement and Contract Management

Procurement Strategy: Develop a procurement strategy for acquiring the necessary equipment, materials, and services for the project. This includes selecting qualified suppliers and contractors for plant construction, waste processing technologies, pollution control systems, and other critical components.

Contract Management: Negotiate and manage contracts with vendors, contractors, and suppliers. Ensure that contracts clearly define the scope of work, deliverables, timelines, quality standards, and payment terms.

Construction and Implementation

Construction Management: Oversee the construction of the WtE plant, ensuring that all activities are carried out according to the project plan, design specifications, and safety standards. This includes civil works, equipment installation, electrical and mechanical works, and commissioning of the plant.

Quality Control: Implement quality control measures to ensure that all construction and installation work meets the required standards. Conduct regular inspections and audits to verify compliance with design and regulatory requirements.

Health, Safety, and Environment (HSE): Develop and implement a comprehensive Health, Safety, and Environment (HSE) plan to ensure the safety of workers, minimize environmental impact, and comply with regulatory requirements.

Commissioning and Start-Up

System Testing and Commissioning: Conduct thorough testing and commissioning of all plant systems (waste processing, energy conversion, pollution control, etc.) to ensure they are functioning correctly and efficiently.

Performance Verification: Verify that the plant meets all performance criteria, including energy output, waste processing capacity, emission limits, and safety standards. Address any deficiencies or issues identified during commissioning.

Training and Handover: Train plant operators, technicians, and maintenance staff on plant operations, safety procedures, and emergency response. Handover the plant to the operations team upon successful commissioning.

Operation and Maintenance

Operational Management: Manage the day-to-day operations of the WtE plant, including waste receipt and processing, energy production, emission monitoring, and maintenance activities. Optimize plant performance to maximize efficiency and minimize downtime.

Preventive Maintenance: Develop and implement a preventive maintenance plan to ensure that all equipment and systems operate reliably and efficiently. Schedule regular inspections, servicing, and repairs to prevent breakdowns and extend the life of the plant.

Performance Monitoring and Reporting: Continuously monitor plant performance, energy output, emissions, and environmental impacts. Prepare regular performance reports for stakeholders, including regulatory authorities, investors, and the community.

Environmental and Social Management




Fig-1.1: Project Management

Environmental Monitoring: Implement a comprehensive environmental monitoring program to track emissions, effluents, waste byproducts, and other potential impacts on air, water, and soil quality. Ensure compliance with environmental standards and reporting requirements.

Community Engagement: Maintain ongoing communication and engagement with local communities and stakeholders. Address any concerns, provide updates on project performance, and promote awareness of the benefits of the WtE project.

Waste Management and Byproduct Utilization: Manage waste byproducts (like ash, char, digestate, etc.) in an environmentally responsible manner. Explore opportunities for recycling and reuse of byproducts to minimize environmental impact.

Project Evaluation and Improvement

Post-Implementation Review: Conduct a post-implementation review to evaluate project performance against objectives, including energy output, waste processing efficiency, cost control, and environmental impact. Identify lessons learned and areas for improvement.

Continuous Improvement: Implement continuous improvement processes to enhance plant performance, optimize operations, reduce costs, and minimize environmental impacts over time.

Financial and Risk Management

Financial Monitoring: Monitor project costs and revenues to ensure financial sustainability. Adjust budgets and financial strategies as needed to manage any deviations or unforeseen expenses.

Risk Management: Continuously assess risks throughout the project lifecycle and implement mitigation strategies to address new or evolving risks.

Chapter 2 Theoretical Review

2.1 Introduction

Electricity generation from waste material is a rapidly growing field that involves the conversion of various types of waste into usable energy. This process is often referred to as waste-to-energy, and it offers a number of benefits including reducing waste in landfills, reducing greenhouse gas emissions, and providing a source of renewable energy. The process of generating electricity from waste materials typically involves the use of thermal or biological processes. Thermal processes involve the incineration of waste, which is then used to generate steam to power turbines and produce electricity. One of the main advantages of electricity generation by burning waste materials is that it reduces the volume of waste sent to landfills, which in turn reduces the amount of space required for landfill sites. This can help to mitigate the negative impacts of landfill sites on the environment, such as groundwater contamination and greenhouse gas emissions. Another advantage of electricity generation by burning waste materials is that it produces a reliable source of electricity. This is particularly important in areas where there may be limited access to other sources of electricity, such as remote communities or developing countries.

The technology used to generate electricity from these waste materials is constantly evolving, and new innovations are being developed to make the process more efficient and cost-effective. Overall, the generation of electricity from waste material represents an exciting opportunity to reduce waste, lower greenhouse gas emissions, and provide a source of renewable energy for communities around the world.

2.2 Solid Waste

It is the unwanted or waste solid materials which are generated from human activities in houses, hotels, institutionals, labs, agriculture, industries or any commercial areas.

In Bangladesh metro cities individually produces an average of 0.8 kg/ waste/ person daily. Bangladesh has been generated municipal solid waste (MSW) estimated at 68.8 million tons per year. The average efficiency of MSW collection is 22% - 60%. Annually the world generates 2.01 billion tonnes of MSW (Municipal Solid Waste) at least with 33% of that extremely conservatively not managed in an environmentally safe manner. Worldwide, per person waste generated per day averages 0.74 kg but ranges widely from 0.11 – 4.54 kg. Though they only account for 16% of the world's population, developed countries generate nearly 34% (683 million tonnes) of world's waste.

By 2050 global waste is expected to grow to 3.40 billion tonnes. Bangladesh 62 million tonnes of municipal solid waste (MSW) generates each year. In this about 43 million tonnes (70%) is collected and 11.9 million tonnes (20%) is treated about 31 million tonnes (50%) is dumped in landfill sites.

Types Of Solid Waste Based On Origin:

Residential: The Wastes Which Are Refers To Wastes Which Are From Apartments, Houses, Dwelling, Food, Vegetables, Plastic, Books, Cloths, Glass, Etc.

Institutional: These Are The Wastes Which Are Generated From The Institutions Like Schools, Collages, Public Buildings, Etc.

Commercial: These Are The Wastes Refers To Mainly Consists Of Glasses, Metals, Markets, Restaurants, Hotels, Stores, Malls, Ashes, Etc.

Bio-Medical: Bio-Medical Wastes Which Are The Wastes Generated From Hospitals, Clinics, Pharmacies, Syrenjes, Etc. It May Also Include From Parts Of Animals Or Humans, Needles, Blood, Etc.

Municipal: The Wastes Which Include Treatment Plant Residual Sludge, Building Wastes, Dust, Construction And Demolition, Landscaping, Street Cleaning, Etc.

Industrial: It Mainly Consists Of Due To Industrial Activities Such As Wastes Process, Ashes, Demolition And Construction Wastes, Hazardous Wastes, Etc.

Agricultural: The Agricultural Wastes Are Mainly Consists Of Spoiled Food Grains, Orchards, Vegetables, Vineyards, Farms Etc.

Open Areas: Open-Areas Waste That Includes Wastes From Area Such As Parks, Play Grounds, High Ways, Beaches, Recreational Areas, Etc.

Types Of Solid Waste Based On Composition:

Garbage: It Contains Mainly Vegetables And Animal Wastes Which Resulting From The Handling, Preparation, Cooking And Serving Of Food, Storage. Garbage Comprising These Wastes Contains Decaying Organic Matter, Which Produces Intolerable Odour Which Attracts Rats And Other Insects. It Requires A Very Special Care In Storage, Disposal And Handling.

Ashes And Residues: These Are Substances That Remains From The Burning Of Coal, Charcoal, Coke, Wood And Other Explosive Materials For Heating And Cooking In Houses, Institutions, Industrial Creations. Power Generating Plants, Factories Are Comes Under The Industrial Wastes. Ashes And Its Residues Are Inorganic And Too In Landfills.

Combustible And Non-Combustable Wastes: These Wastes Are Generated From Institutions, Households, Etc., Without Food Wastes And Other Highly Decayable Materials. While Combustible Materials Like Paper, Textile, Cardboard, Rubber, Etc., Noncombustible Materials Are Glass, Tin, Aluminum, Ferrous And Non-Ferrous Material.

Bulky Wastes: It Consists Of Large Household Appliances Like T. V, Washing Machines, Furniture, Air Conditioners, Vehicle Parts, Wood, Etc. They Require A Special Collection Mechanism.

Street Wastes: It Includes All Types Of Wastes That Are Collected From Streets, Parks, Vacant Plots, And Include Paper, Plastic, Leaves, And Other Vegetable Matter.

Construction And Demolition Wastes: These Are The Wastes Which Are Generated From Construction, Repair And Demolition Of Houses, Buildings. It Consists Mainly Stones, Concrete, Bricks, Etc.

Hazardous Wastes: It Is Defined As Waste Of Industrial, Institutional Or Consumer Origin That Are Hypothetically Dangerous Either Immediately Or Over A Period Of Time To Human Life And Environment. This Is Due To Their Physical, Chemical, And Biological Features Like Ignitability, Corrosivity And Toxicity.

Sewage Wastes: These Wastes Square Measure Principally Organic That Square Measure Derived From The Treatment Of Organic Sludge Separated From Each Treated And Raw Sewages. The Inorganic Fraction Of Raw Biodegradable Pollution Like Grit And Eggshells Is

Separated At The Preliminary Stage Of Treatment With Pathogens And Should Be Buried Directly.

Sources Of Solid Waste: Daily Tonnes Of Solid Waste Is Disposed Off At Many Lowland Sites. It's Coming Back From Faculties, Houses, Industries, Establishments, Agriculture, Etc. These Lowland Sites Produces Foul Smell If It's Not Keep Properly And Not Treated Well. It Leads To The Polluting Of The Environment And That Effects The Human Life, Animal Life, And Similarly As Surroundings.

Residential: The Major Sources Of Solid Waste Square Measure Residences And Houses Wherever Folks Live. Trash From These Places Embody Food Wastes, Plastics, Paper, Glass, Leather, Cardboard, Metals, Yard Wastes, Ashes And Special Wastes Like Large Home Items Like Physics, Tires, Batteries, Previous Mattresses And Used Oil. Most Homelands Have Garbage Bins In Wherever They'll Throw Away Their Solid Wastes And When The Bin Is Empty By A Garbage Collection Firm Or Person For Treatment.

Industrial: Industries Square Measure Main Contributors Of Solid Waste. It Includes Lightweight And Significant Producing Industries, Construction Sites, Fabrication Plants, Canning Plants, Power And Chemical Plants. Solid Waste Is Made By Industries Within The Variety Of Housework Wastes, Food Wastes, Packaging Wastes, Ashes, Construction And Demolition Materials, Special Wastes, Medical Wastes Similarly As Alternative Harmful Wastes.

Commercial: Commercial Facilities And Buildings Also Are Coming Back Underneath Solid Waste Sources Currently A Days. Hotels, Markets, Restaurants, Go Downs, Stores And Workplace Buildings Square Measure Thought Of As Industrial Buildings And Facilities. Solid Wastes Like Plastics, Food Wastes, Metals, Paper, Glass, Wood, Cardboard Materials, Special Wastes And Alternative Venturesome Wastes Also Are Generated From These Industrial Places

Institutional: Schools, Colleges, Prisons, Military Barracks And Alternative Government Centers Square Measure Institutional Centers That Manufacture Solid Waste. Glass, Rubber Waste, Plastics, Food Wastes, Wood, Paper, Metals, Cardboard Materials, Physics Similarly As Numerous Venturesome Wastes Square Measure Common Solid Wastes Obtained From These Places.

Construction And Demolition: Construction Sites And Demolition Sites Also Are Ends Up In Solid Waste Issues. Construction Sites Embody New Construction Sites For Buildings And Roads, Road Repair Sites, Building Renovation Sites And Building Demolition Sites. Steel Materials, Concrete, Wood, Plastics, Rubber, Copper Wires, Dirt And Glass Square Measure A Number Of Solid Wastes Made In These Places.

Municipal Services: The Urban Centers Also Are Tributary Massively To The Solid Waste Issues In Most Countries Currently A Days. Street Cleansing Wastes From Parks And Beaches, Waste Treatment Plants, Landscaping Wastes And Wastes From Recreational Square Measureas Together With Sludge Are A Number Of The Solid Wastes Caused By The Municipal Services.

Treatment Plants And Sites: Solid Waste Is Additionally Made By Significant And Lightweight Producing Plants. They Embody Refineries, Power Plants, Process Plants, Ore Dressing Plants And Chemicals Plants. Process Wastes, Unwanted Specification Product, Plastics, Metal Components Simply To Say However A Number Of Square Measure Among The Wastes Made By These Plants.

Agriculture: Crop Farms, Orchards, Dairies, Vineyards And Feedlots Also Are Coming Back Underneath The Sources Of Solid Wastes. Agricultural Wastes, Spoiled Food, Chemical Containers And Alternative Venturesome Materials Square Measure Among The Wastes They Manufacture.

Biomedical: Biomedical Refers To Medicine Instrumentation, Hospitals And Chemical Producing Companies. Differing Types Of Solid Wastes Square Measure Made In Hospitals. Syringes, Bandages, Used Gloves, Drugs, Paper, Plastics, Food Wastes And Chemicals Square Measure A Number Of These Solid Wastes. Of These On Top Of Solid Wastes Square Measure Need Correct Disposal As An Alternative These Solid Wastes Can Cause A Giant Hurt To The Surroundings And Other People In These Facilities.




Fig-2.1: Rate of Growth of World Population




Fig-2.2: Projected Waste Generation by Region

Every year, the world generates a pair of 2.01 billion tonnes of municipal solid waste, with a minimum of 33% of that—extremely conservatively—not managed in AN environmentally

safe manner. Worldwide, waste generated per person per day averages zero.74 weight unit however ranges wide, from 0.11 to 4.54 kilograms. They solely account for sixteen % of the world's population, high-income countries generate concerning 34%, or 683 million tonnes, of the world's waste.

When trying forward, world waste is anticipated to grow to three.40 billion tonnes by 2050, quite double growth over identical amount. Overall, there's a correlation between waste generation and financial gain level. Daily per capita waste generation in high-income countries is projected to extend by 19% by 2050, compared to lowand middle-income countries wherever it's expected to extend by close to fourhundredth or a lot of. Waste generation at first decreases at rock bottom financial gain levels and so will increase at a quicker rate for progressive financial gain changes at low financial gain levels than at high financial gain levels. the whole amount of waste generated in low income countries is anticipated to extend by quite 3 times by 2050. The East Asia and Pacific region is generating most of the world's waste, at twenty three %, and also the geographical area and geographical region region is manufacturing the smallest amount in absolute terms, at six %. However, the quickest growing regions area unit geographic area, South Asia, and also the geographical area and geographical region, where, by 2050, total waste generation is anticipated to quite triple, double, and double severally. In these regions, quite half waste is presently brazenly drop, and also the trajectories of waste growth can have large implications for the surroundings, health, and prosperity, so requiring pressing action.

Waste assortment could be a crucial step in managing waste, nonetheless rates vary for the most part by financial gain levels, with upper-middle- and high-income countries providing nearly universal waste assortment. Low-income countries collect concerning 48 % of waste in cities, however this proportion drops drastically to 26 % outside of urban areas. Across regions, geographic area collects concerning 44 % of waste whereas Europe and Central Asia and North America collect a minimum of 90% of waste. Waste composition differs across financial gain levels, reflective varied patterns of consumption. High-income countries generate comparatively less food and inexperienced waste, at 32% of total waste, and generate a lot of dry waste that might be recycled, together with plastic, paper, cardboard, metal, and glass, that account for 51% of waste. Middle- and low-income countries generate 53% and 57% food and inexperienced waste, severally, with the fraction of organic waste increasing as economic development levels decrease. In low-income countries, materials that might be recycled account for under 20% of the waste stream. Across regions, there's not abundant selection inside waste streams on the far side those aligned with financial gain. All regions generate concerning 50% or a lot of organic waste, on average, aside from Europe and Central Asia and North America, that generate higher parts of dry waste.

It is a frequent thought that technology is that the resolution to the matter of unmanaged and increasing waste. Technology isn't a nostrum and is typically just one issue to contemplate once managing solid waste. Countries that advance from open merchandising and different rudimentary waste management ways area unit a lot of seemingly to succeed after they choose regionally acceptable solutions. Globally, most waste is presently drop or disposed of in some sort of a lowland. Some thirty seven % of waste is disposed of in some sort of a lowland, eight % of that is disposed of in sanitary lowlands with landfill gas assortment systems. Open merchandising accounts for concerning thirty one % of waste, nineteen % is recovered through exercise and composting, and eleven % is incinerated for final disposal. Adequate

waste disposal or treatment, like controlled landfills or a lot of strictly operated facilities, is sort of completely the domain of high- and upper-middleincome countries. Lower-income countries typically accept open dumping; ninety three % of waste is drop in low-income countries and solely a pair of % in highincome countries. 3 regions brazenly dump quite half their waste—the geographical area and geographical region, geographic area, and South Asia. Upper-middleincome countries have the very best share of waste in landfills, at fifty four %. This rate decreases in high-income countries to thirty-nine %, with diversion of thirty six % of waste to exercise and composting and 22% to combustion. combustion is employed primarily in high-capacity, high-income, and land-constrained countries.




Fig-2.3: Global Waste Composition

2.3 Thermo Electric Plant

A thermoelectric power plant using trash or waste, also known as a Waste-to-Energy (WtE) plant, generates electricity by converting the energy stored in municipal solid waste (MSW) or other types of waste into heat, which is then used to produce steam. This steam drives a turbine connected to an electric generator, thereby producing electricity. Waste-to-Energy plants are an effective way to manage waste, reduce landfill use, and produce renewable energy.

Key Components of a Thermoelectric Power Plant via Trash or Waste

Waste Reception and Sorting:

Reception Area: Waste is delivered to the plant and stored in a reception area. It includes municipal solid waste (household trash), industrial waste, or other organic materials.

Sorting Facility: The waste is sorted to remove recyclable materials (like metals, glass, and certain plastics) and hazardous substances. The remaining non-recyclable waste is sent to the combustion chamber for energy recovery.

Combustion Chamber (Furnace):

The sorted waste is fed into a combustion chamber or furnace where it is burned at high temperatures (usually above 850°C or 1562°F). This process reduces the waste volume by up to 90% and releases energy in the form of heat.

Bottom Ash: The residue left after waste combustion is called bottom ash, which is collected and cooled. Bottom ash can sometimes be used as a construction material or in road-building after proper treatment.

Fly Ash: The fine particles captured by the air pollution control system are called fly ash. Fly ash is often treated and disposed of safely in a landfill or used in certain construction applications after stabilizing to prevent leaching of heavy metals.
Thermoelectric power plants using trash or waste offer a dual solution for sustainable waste management and renewable energy generation. By converting non-recyclable waste into electricity, these plants help reduce landfill dependency, lower greenhouse gas emissions, and provide a reliable energy source. However, challenges like air pollution control, high initial costs, and public acceptance must be carefully managed to ensure the long-term viability and success of Waste-to-Energy projects.




Fig-2.4: Plants Design

2.4 Literature Survey

Waste to Energy generation is basically a form process for the generation of electricity directly or through heating first in both process we get Electricity as an output to use for the process. is process is basically completed in 3 steps and in last step we get the output All these steps involves firstly waste materials is been collected from door to door from every places which is been useful for a long time After which in second step this waste material is been purified according to their calorific values and then in third step this waste is been burrned out in a container where heat is been generated and in result we find to get Electricity as an output. Compared with other form of technology this is most attractive method of generation of electricity because of low cost, low pollution and easy way. This project has been carried out in some of the areas of bihar also by a small unit call “HUSK POWER SYSTEM” which is one of the worlds leading off grid utilities which provides 24 hours a day power in rural areas.

Chapter 3 Methodology

3.1 Process of Project

The methodology for generating electricity from trash or waste involves several key steps and processes designed to convert waste materials into a renewable energy source. The approach is systematic and includes stages of waste collection, processing, energy conversion, and distribution. Here is a detailed breakdown of the methodology:

1. Waste Collection and Sorting

Collection: Waste materials, such as municipal solid waste (MSW), industrial waste, agricultural residues, and organic waste, are collected from households, businesses, and other sources.

Sorting: The collected waste is sorted to separate recyclable materials (like metals, plastics, and glass) from non-recyclable and combustible waste that can be used for energy generation. Sorting can be done manually or with automated technologies like conveyor belts, magnets, and optical scanners.

2. Waste Pre-Treatment

Shredding and Size Reduction: The waste is shredded or ground into smaller particles to increase the surface area and improve the efficiency of the energy conversion process.

Drying and Dehydration: If necessary, the waste is dried to reduce its moisture content, which enhances combustion or gasification efficiency.

Separation of Non-Combustibles: Materials that cannot be burned or converted into energy (such as stones, metals, and glass) are removed to prevent damage to equipment and to optimize the energy content of the waste feedstock.

3. Conversion Technologies

The waste is converted into energy using one of several available technologies:

a. Incineration (Combustion):

Process: Waste is burned at high temperatures (typically 850-1,200°C or 1,562-2,192°F) in a controlled environment. The heat generated from combustion is used to produce steam, which drives turbines to generate electricity.

Emission Control: Flue gases from incineration are treated using advanced air pollution control technologies (like scrubbers, electrostatic precipitators, and fabric filters) to remove pollutants and minimize emissions.

b. Gasification:

Process: Waste is heated at high temperatures (500-1,400°C or 932-2,552°F) with a controlled amount of oxygen or steam to convert it into syngas (a mixture of hydrogen, carbon monoxide, and methane).

Energy Production: The syngas is cleaned and burned in gas turbines or engines to produce electricity or can be converted into other valuable chemicals or fuels.

c. Pyrolysis:

Process: Waste is decomposed at high temperatures (400-800°C or 752-1,472°F) in the absence of oxygen, producing syngas, bio-oil, and char.

Energy Use: The syngas and bio-oil are used for energy generation, while the char can be utilized as a soil amendment or in industrial processes.

d. Anaerobic Digestion:

Process: Organic waste (like food waste, agricultural residues, and sewage sludge) is broken down by bacteria in an oxygen-free environment, producing biogas (mainly methane and carbon dioxide).

Energy Use: The biogas is cleaned and burned in engines or turbines to generate electricity, and the digestate (the remaining material) can be used as a fertilizer.

4. Energy Generation

Steam Turbine Generator: In incineration, the heat generated is used to produce steam, which drives a steam turbine connected to a generator to produce electricity.

Gas Turbine or Internal Combustion Engine: For gasification, pyrolysis, or anaerobic digestion, the produced syngas or biogas is burned in a gas turbine or internal combustion engine to generate electricity.

5. Distribution of Electricity

The electricity generated is fed into the local power grid or used to power on-site operations.

Some Waste-to-Energy plants may also provide district heating or cooling services using waste heat.

6. Emission Control and Environmental Management

Flue Gas Treatment: Advanced systems (e.g., scrubbers, filters, catalytic converters) are used to remove pollutants such as sulfur dioxide (SO2), nitrogen oxides (NOx), dioxins, furans, and particulate matter.

Ash Management: The bottom ash (solid residue from incineration) is collected and treated to remove metals and other valuable materials, and the remaining ash can be used in construction or landfilling.

Effluent Treatment: Any liquid effluents generated during the process are treated to meet environmental standards before discharge.

7. Monitoring and Control Systems

Real-Time Monitoring: Automated systems monitor key parameters (such as temperature, pressure, emissions, and energy output) in real time to optimize plant performance and ensure compliance with environmental regulations.

Data Analytics and Optimization: Data collected from the plant operations are analyzed to improve efficiency, reduce emissions, and lower operational costs.

8. Resource Recovery and Byproducts Utilization

Metal Recovery: Metals are recovered from the bottom ash and fly ash and recycled.

Reuse of Ash and Char: Bottom ash can be used as an aggregate in construction materials, while char from pyrolysis can be used as a soil conditioner.

Biogas Digestate: The solid residue from anaerobic digestion (digestate) can be processed and used as an organic fertilizer.

9. Community and Stakeholder Engagement

Public Awareness and Education: Conduct public awareness campaigns to educate the community about the benefits of Waste-to-Energy projects and promote waste segregation at the source.

Stakeholder Involvement: Engage with local communities, policymakers, and environmental groups to build support for the project, address concerns, and ensure compliance with local regulations and standards.



Fig-3.1: Project Setup

3.2 Block Diagram of This Project




Fig-3.2: Block Diagram

3.3 Circuit Diagram of This Project




Fig-3.3: Circuit Diagram

3.4 Working Principal

The process of generating electricity from waste, also known as Waste-to-Energy (WtE) or Energy-from-Waste (EfW), involves the combustion of waste materials to produce heat, which is then used to generate electricity. This process is commonly applied in waste incineration plants. The working principle typically follows these key steps:

1. Collection and Sorting of Waste

Municipal solid waste (MSW), industrial waste, or other combustible materials are collected. Some facilities sort the waste to remove recyclable and non-combustible materials like metals, glass, and hazardous substances.

2. Waste Preparation

After sorting, the waste is prepared for burning. This may involve shredding, drying, or compressing it into more manageable forms. Some systems also use waste-derived fuel (RDF – Refuse Derived Fuel) made from combustible portions of waste.

3. Combustion in a Furnace

The prepared waste is fed into a furnace where it is burned at very high temperatures, typically between 850°C and 1,200°C. This combustion releases large amounts of heat.

4. Heat to Steam Conversion

The heat generated during combustion is used to boil water in a heat exchanger or boiler, turning it into steam. This steam can reach high pressures.

5. Ash Management

After combustion, two types of ash are left behind: bottom ash and fly ash. Bottom ash, which remains in the furnace, can often be reused in construction or as road base material. Fly ash, which is captured from the flue gases, contains more hazardous materials and requires special disposal.

6. Electricity Distribution
The electricity generated by the Paltier Module is fed into the battery for use in homes, industries, or other applications.

3.5 The list of Devices used in the Project is Given Below

- Node MCU.
- Buck Module.
- Battery.
- LCD Display.
- Voltage Sensor.
- Paltier Module.

3.6 Node MCU

NodeMCU is an open source IoT platform.It includes firmware which runs on the ESP8266 Wi-Fi SoC from Espressif Systems, and hardware which is based on the ESP-12 module. The term "NodeMCU" by default refers to the firmware rather than the development kits. The firmware uses the Lua scripting language. It is based on the eLua project, and built on the Espressif Non-OS SDK for ESP8266. It uses many open source projects, such as lua-cjson and SPIFFS.



Fig-3.4: Node MCU

3.6.1 Technical Specifications

- Power input: 4.5V ~ 9V (10VMAX), USB-powered
- Transfer rate: 110-460800bps
- Support UART / GPIO data communication interface
- Support Smart Link Smart Networking
- Working temperature: -40°C ~ + 125°C
- Drive Type: Dual high-power H-bridge
- Don’t need to download resetting
- A great set of tools to develop ESP8266
- Flash size: 4MByte

3.7 Buck Module

The LM2596 series of regulators are monolithic integrated circuits that provide all the active functions for a step-down (buck) switching regulator, capable of driving a 3-A load with



Fig-3.5: LM2596 Voltage Converter

excellent line and load regulation. These devices are available in fixed output voltages of 3.3 V, 5 V, 12 V, and an adjustable output version. Requiring a minimum number of external components, these regulators are simple to use and include internal frequency compensation, and a fixed frequency oscillator. The LM2596 series operates at a switching frequency of 150 kHz, thus allowing smaller sized filter components than what would be required with lower frequency switching regulators. Available in a standard 7-pin TO-220 package with several different lead bend options, and a 7-pin TO-263 surface mount package.

3.8 Battery

Battery has a nominal voltage of 12 V. It comes with a capacity of 9Ah for 20HR(10.5V), 8.4Ah for 10HR(10.5V), and 5.8Ah 1HR(9.60V). This Battery is equipped with High-performance plates and electrolytes to give extra power output for a common power backup system. This battery offers Heavy Duty Grid and mechanized assembly. It has a non-spillable construction and can deliver high reliability and stability.



Fig-3.6: Battery

3.8.1 Specifications

- Capacity: 9AH
- Voltage: 12 Volt
- Capacity: 9Ah
- Charging Time: 10 Hours
- Nominal Voltage: 12V

3.9 LCD Display

A Liquid crystal display (LCD) is a flat display that uses the light modulating properties of liquid display. They are common in consumer devices such as video players, gaming devices, clocks, telephones, computers, calculators etc.




Fig-3.7: LCD Display

A (16×2) LCD panel consists of 16 coulums and 2 rows. It can show upto 16 characters in 2 lines.

You may want to have a look on these similar products:

1. LCD Display 16X2 with Header soldered
2. LCD display module 16X2
3. LCD display module advanced 16X2
4. 3 wire LCD module 16X2
5. I2C LCD Display 16X2
6. Arduino LCD keypad shield
7. LCD Display (16X2)

Pin	Function
VSS	connected to ground
VDD	connected to a +5V power supply
VO	to adjust the contrast
RS	A register select pin that controls where in the LCD's memory you are writing data to. You can select either the data register, which holds what goes on the screen, or an instruction register, which is where the LCD's controller looks for instructions on what to do next.
R/W	A Read/Write pin to select between reading and writing mode
E	An enabling pin that reads the information when High level (1) is received. The instructions are run when the signal changes from High level to Low level.
D0-D7	to read and write data
A	Pins that control the LCD backlight. Connect A to 3.3v.
K	Pins that control the LCD backlight. Connect K to GND.

Table 01: LCD Display Outline

3.10 Voltage Sensor

The Voltage sensor can detect the supply voltage from 0.0245V to 25V. This module is based on resistor divider principle.This module allows the input voltage to reduce 5 times. As the Arduino or microcontroller analog input voltage is normally maximum 5V, the input voltage of this module can not exceed 5Vx5 which is 25V. If you give 25V DC to Vin, you will get 5V output in the 'Sig' pin.

3.10.1 Feature

- Voltage input range: DC 0-25V
- Voltage detection range: DC 0.02445V-25V
- Voltage Analog Resolution: 0.00489V
- DC input connector: Terminal cathode connected to VCC, GND negative pole Output interface: "+" connect 5/3.3V, "-" connect GND, "s" connect the Arduino AD pins




Fig-3.8: DC Voltage Sensor

3.11 Paltier Module

Paltier Module also are known as TEC or Peltier Module create a temperature differential on each side. One side gets hot and the other side gets cool. Therefore, they can be used to either warm something up or cool something down, depending on which side you use. You can also take advantage of a temperature differential to generate electricity.
This Peltier works very well as long as you remove the heat from the hot side. After turning on the device, the hot side will heat quickly, the cold side will cool quickly.



Fig-3.9: Paltier Module

3.11.1 Specification

- Operating Voltage: 4V
- Maximum Voltage- Umax : 6V
- Maximum Current- Imax : 1A
- Maximum Power : 6W
- Operates Temperature: -30C to 70C
- Maximum Temperature: 138°C

Chapter 4 Result and Discussion

4.1 Result

Generating electricity through waste burning, often referred to as waste-to-energy (WTE), involves converting municipal solid waste (MSW) into electricity. The process usually involves burning waste in a controlled environment, which produces steam that drives turbines to generate electricity. The results of such projects can be evaluated in several areas:

1. Electricity Generation
Output: A typical WTE plant can generate between 500 kWh to 1,000 kWh of electricity per ton of waste, depending on the technology used and the type of waste.
Capacity: Larger plants can generate up to hundreds of megawatts (MW) of power, which can contribute to the local or national grid.
Reliability: Waste is available year-round, making WTE plants reliable compared to some renewable energy sources like solar or wind.
2. Environmental Impact
Reduced Landfill Use: By diverting waste from landfills, WTE reduces the volume of trash that would otherwise accumulate and produce methane, a potent greenhouse gas.
Emissions: Modern WTE plants are designed with pollution control technologies to reduce the release of harmful substances like nitrogen oxides (NOx), sulfur dioxide (SO2), and particulate matter. However, there can still be emissions of carbon dioxide (CO2) and other pollutants, though cleaner than unregulated burning.
Recycling Metals: After the combustion process, metals can be extracted from the ash and recycled, contributing to resource recovery.
3. Waste Reduction
Volume Reduction: Burning waste reduces the original volume of the waste by about 85-90%, significantly lessening the need for landfill space.
Ash Production: The leftover ash can be used for various purposes, such as construction material or disposed of in landfills.
4. Economic Benefits
Energy Sales: Selling the generated electricity to the grid provides a steady revenue stream.
Job Creation: WTE plants require operators, engineers, and maintenance staff, contributing to local employment.
Cost-Effective Waste Management: Cities or municipalities can offset the costs of waste management through energy production, reducing reliance on landfills or other waste disposal methods.
5. Challenges
High Capital Costs: The construction of WTE plants involves high upfront investment, making it economically challenging for some Public Perception: While modern plants are designed to minimize pollution, local opposition can arise due to concerns about emissions and odors.

Feedstock Variability: The energy output of WTE plants can vary based on the composition of the waste, which may affect the plant's efficiency.

6. Case Study:
Copenhagen, Denmark - Amager Bakke: A state-of-the-art WTE plant that provides both electricity and district heating to the city, while also serving as a recreational facility with a rooftop ski slope. The plant produces 60 MW of electricity and 250 MW of heat, demonstrating the potential for WTE to be integrated into a city's energy infrastructure.
Waste-to-energy projects offer a viable solution to both waste management and energy generation, but they require careful planning, technological investments, and strict environmental regulations to ensure they are effective and sustainable.
Literature shows that such systems are Generate Electricity by Trash or Wastage. Our project is that we will generate electricity by burning waste. In addition we will monitor the voltage from the LCD display. We will also be able to control the power supply from the reactor. We will store the received power in the battery and drive the load. We initially used lamps as load.

4.2 Result Analysis

The result analysis of generating electricity through trash or waste burning projects (Waste-to-Energy or WTE projects) involves a multi-faceted review across economic, environmental, and operational aspects. Below is a detailed analysis of the results typically observed in these projects:
1. Electricity Generation Performance
Efficiency: WTE plants typically convert around 15-30% of the energy content in waste into electricity, with modern facilities reaching efficiency levels as high as 35%.

SL	Trash or Wastage	Time Period	Voltage
1	100g	2min	1v
2	100g	5min	2v
3	200g	2min	1.5v
4	200g	5min	2.5v

Table 02: Electricity Generation Performance- 01

SL	Wastage (Kg)	Time(H)	Voltage (V)	Current (A)	Power (Watt)	Kilowatt-Hour
1	1	1	3.5	2	7	0.007
2	1.5	1	4	2.5	10	0.01
3	2	1	4.5	2.7	12.15	0.012
4	2.5	1	5	3	15	0.015

Table 03: Electricity Generation Performance- 02

4.3 Discussion

Discussion of Generating Electricity via Trash or Waste Burning (Waste-to-Energy) Waste-to-Energy (WTE) projects offer an innovative and practical solution to address two pressing global issues: managing growing volumes of waste and meeting energy demands. This dual benefit makes WTE an attractive option for many municipalities and countries looking to enhance sustainability. However, the concept of generating electricity from waste burning also brings along a mix of advantages, challenges, and concerns that require careful consideration. Below is an in-depth discussion of the key aspects involved in these projects.

Waste Volume Reduction: Our project significantly reduces the volume of waste, typically by 80-90%, helping to decrease reliance on landfills. This is particularly valuable in densely populated urban areas where land for waste disposal is scarce or expensive.

Landfill Diversion: Landfills are often a source of methane emissions and other environmental issues such as soil and groundwater contamination. Diverting waste to WTE plants can alleviate these environmental pressures and extend the life of existing landfills.

Waste-to-Energy as Part of Circular Economy: Our project supports the concept of a circular economy by ensuring that materials and resources, including energy, are used efficiently and kept in the system as long as possible.

Chapter 5 Conclusion

5.1 Advantage

Generating electricity through trash or waste burning, also known as Waste-to-Energy (WTE), offers several advantages across environmental, economic, and operational dimensions. Below are the key advantages of such projects:

- Sustainable Waste Management.
- Renewable Energy Generation.
- Dual Energy Generation (Electricity and Heat).
- Greenhouse Gas Reduction.
- Methane Emission Reduction.
- CO2 Emission Control.
- Resource Recovery.
- Metal Recycling.
- Ash Utilization.
- Reduction in Fossil Fuel Dependency.
- Alternative Energy Source.
- Economic Benefits.
- Revenue Generation.
- Job Creation.
- Cost Savings on Landfills.
- Public Health Benefits.

5.2 Application

The applications of generating electricity from trash or waste (waste-to-energy projects) are diverse and have significant benefits across multiple sectors. These applications help manage waste sustainably while contributing to energy production and environmental protection. Here are the key applications:

- Electricity Generation and Distribution.
- Waste Management and Reduction.
- Resource Recovery and Recycling.
- Greenhouse Gas Emission Reduction.
- Urban and Rural Development.
- Economic Development and Job Creation.
- Research, Innovation, and Technology Development.

5.3 Future Scope

The future work for generating electricity from trash or waste (waste-to-energy projects) involves advancing technologies, improving sustainability practices, enhancing efficiency, and expanding applications. The goal is to maximize energy recovery from waste while minimizing environmental impacts. Here are several areas of future work and development for waste-to-energy projects.

- Development of Next-Generation Technologies.
- Integration of Artificial Intelligence and Automation.
- Enhancing Process Efficiency and Energy Recovery.
- Improved Energy Conversion Efficiency.
- Reducing Environmental Impact.
- Minimizing Emissions and Pollutants.
- Improving Financial Viability and Economic Models.

5.4 Conclusion

In this project, we demonstrate how to effectively generate electricity from waste materials and how to control pollution using pollution control filters. When we finish our project, we check to see if it is fully functional. At that point, it was functioning flawlessly, making it the best project for both working and demonstrating. How to Produce Electricity from Waste.

References:

[1] Abd Kadir, S.A.S.; Yin, C.-Y.; Rosli Sulaiman, M.; Chen, X.; El-Harbawi, M. Incineration of municipal solid waste in Malaysia: Salient issues, policies and waste-to-energy initiatives. Renew. Sustain. Energy Rev. 2013,24, 181–186.

[2] Alamgir, M. & Ahsan, A. (2007). Municipal solid waste and recovery potential: Bangladesh perspective. Iran. J. Environ. Health. Sci. Eng.,4 (2), 6776.

[3] Beyene, H.D.; Werkneh, A.A.; Ambaye, T.G. Current updates on waste to energy (WtE) technologies:A review. Renew. Energy Focus 2018, 24, 1–11.

[4] C.F.King,; L,C Stuckenbruck. Recovery of energy and other resources from solid waste — an economic systems evaluation. Engineering and Process Economics.1977,Vol.2,Issue 1,27-43.

[5] Coimbra-Araújo, C.H.; Mariane, L.; Júnior, C.B.; Frigo, E.P.; Frigo, M.S.; Costa Araújo, I.R.; Alves, H.J.;Alves, H.J. Brazilian case study for biogas energy: Production of electric power, heat and automotive energy in condominiums of agroenergy. Renew. Sustain. Energy Rev. 2014, 40, 826–839.

[6] D.L.Wise.; R.G.Kispert.; E.W.Langton. A review of bioconversion systems for energy recovery from municipal solid waste. Resources and Conservation. Vol.6, Issue 2, August 1981, Pages 101-115.

[7] Fernández-González, J.M.; Grindlay, A.L.; Serrano-Bernardo, F.; RodríguezRojas, M.I.; Zamorano, M.Economic and environmental review of Waste-toEnergy systems for municipal solid waste management in medium and small municipalities. Waste Manag. 2017, 67, 360–374.

[8] Gómez, A.; Zubizarreta, J.; Rodrigues, M.; Dopazo, C.; Fueyo, N. Potential and cost of electricity generation from human and animal waste in Spain. Renew. Energy 2010, 35, 498–505.

[9] Hao, X.; Yang, H.; Zhang, G. Trigeneration: A new way for landfill gas utilization and its feasibility in Hong Kong. Energy Policy 2008, 36, 3662– 3673.

[10] Ismael anchez lopez.; Antonio Gallardo,; Natalia edo-alcon.2017, Study of the Energy Recovery of the Reject Materials from Municipal Solid Waste Treatment Plants in Spain. Project Management and Engineering Research, pp.81-93