# DESIGN AND CONSTRUCTION OF A HIGH SPEED FOUR WAY MULTI PURPOSE MACHINE (CUTTING, DRILLING AND GRINDING)

A thesis report submitted for the partial fulfillment

of the requirements for the degree of B.Sc. in Mechanical Engineering


**Submitted by:**

MD: Maniruzzaman (ME2103025323)
Rashedul Islam (ME2103025169)
Md: Momin Chowdhury (ME2103025337)
MD: Roman Mia (ME2103025339)
MD:Abdul Momin (ME2103025489)

Supervised by:
**M. I. Washif Rahman**
Lecturer

**DEPARTMENT OF MECHANICAL ENGINEERING**
**SONARGAON UNIVERSITY**





**May, 2025**

# DECLARATION

This is hereby declared that this project work has been performed by us under the Supervision of **M. I. Washif Rahman** and this thesis or any part of it has not been submitted elsewhere for any award of any degree.

**Signature of the Supervisor**

_____

**M. I. Washif Rahman**
**Lecturer**
**Department of Mechanical Engineering**

**Sonargaon University**

**Signature of the Student**

_____
Md. Maniruzzaman
ID: ME2103025323

_____
Rashedul Islam
ID: ME2103025169

_____
Md. Momin Chowdhury
ID: ME2103025337

_____
Md. Roman Mia
ID: ME2103025339

_____
Md. Abdul Momin
ID: ME2103025489

# ACKNOWLEDGEMENT

Firstly, we want to express gratefulness and humbleness to Almighty Allah for His immense blessing upon me for the successfulness completion of this thesis work. We would like to express my sincere gratitude to my supervisor**, M. I. Washif Rahman**. Lecturer, Department of Mechanical Engineering, Sonargaon University for his valuable suggestions, guidance and constant encouragement during pursuit of this work.

We express our deep sense of gratitude and thanks to Professor **Md. Mostofa Hossain**, Head, Department of Mechanical Engineering, and Sonargaon University for his motivation and kind collaboration.

Finally, we would like to express my sincere gratitude to my family who have given support to my study and prayed for my life.

# ABSTRACT

This thesis presents the design and construction of a high-speed, four-way multipurpose machine capable of performing cutting with disc & hacksaw, drilling, and grinding operations simultaneously. The objective is to increase productivity, reduce operational costs, and conserve space and energy in small to medium scale industrial applications. The machine integrates multiple functions into a single system using a shaft-driven mechanism powered by a 2 HP motor, with power transmitted through pulleys and belts, including a Scotch-Yoke mechanism for the hacksaw operation. Real-time experimental tests were conducted on three commonly used materials: wood, aluminum, and mild steel. For wood, observed temperatures ranged from 32°C to 42°C during sawing, 32°C to 45°C during drilling, and 32°C to 102°C during grinding. For aluminum, temperatures ranged from 32°C to 42°C for sawing, 32°C to 40°C for drilling, and 32°C to 52°C for grinding. In the case of steel, temperature variations were noted as 32°C to 44°C during sawing, 32°C to 48°C during drilling, and 32°C to 60°C during grinding. These results validate the machine's functionality across a spectrum of materials and confirm its ability to operate under thermal stress within a manageable range. The proposed system proves to be a cost-effective, space-efficient, and versatile solution for industries requiring multi-operation capabilities, particularly where resource optimization is critical. The machine design holds potential for further enhancements such as speed regulation, tool change mechanisms, and automation features.

# TABLE OF CONTENT


Chapter 1 ..... 1

1.1 INTRODUCTION ..... 1

1.2 LITERATURE REVIEW ..... 1

1.3 OBJECTIVES ..... 2

1.4 EXPERIMENTALWORK ..... 2

Chapter 2 ..... 4

2.1 METHODOLOGY ..... 4

2.2 WORKING PRINCIPLE ..... 4

2.3 PROBLEM STATEMENT ..... 5

Chapter 3 ..... 7

3.1 PROJECT COMPONENTS NAME ..... 7

3.2 MEASUREMENT OF THE MACHINE ..... 8

3.3 CALCULATIONS ..... 8

Chapter 4 ..... 10

4.1 DIAGRAM OF THE PROJECT ..... 10

4.2 TECHNICAL DIMENSION OF THE PROJECT: ..... 10

4.3 MAIN COMPONENTS USED IN MULTIPURPOSE MACHINE ..... 11

Chapter 5 ..... 17

5.1 EXPERIMENTAL DATA ..... 17

5.2 RESULT ANALYSIS ..... 20

Chapter 6 ..... 21

6.1 CONCLUSION ..... 21

6.2. FUTURE RECOMMENDATIONS ..... 21

Chapter 7 ..... 23

# LIST OF FIGURES

Figure 1.1: Conceptual Visualization of the Project ..... 3
Figure 2.1: Flow Chart of Methodology ..... 4
Figure 2.2: Scotch-Yoke mechanism for Hacksaw frame ..... 5
Figure 3.1: 3D Design Prototype for the Multipurpose Machine ..... 7
Figure 4.1: 3D CAD Model of the Project ..... 10
Figure 4.2: Technical Dimensions ..... 10
Figure 4.3: Drill Chuck with drill bit ..... 11
Figure 4.4: Hacksaw frame with blade ..... 11
Figure 4.5: Cutting disc ..... 13
Figure 4.6: Grinding Wheel ..... 13
Figure 4.7: Pillow Bearing Block ..... 14
Figure 4.8: Motor Construction ..... 14
Figure 4.9: V belt Pulley ..... 15
Figure 4.10: Driver and Driven pulley with v-belt ..... 16
Figure 5.1: Graph Chart of Experimental Sawing Operation ..... 17
Figure 5.2: Graph Chart of Experimental Drilling Operation ..... 18
Figure 5.3: Graph Chart of Experimental Grinding Operation ..... 19

# LIST OF TABLES

Table 5.1: Experimental Data Analysis - Automatic Sawing (Cutting) Operation ..... 17
Table 5.2: Experimental Data Analysis - Automatic Drilling Operation ..... 18
Table 5.3: Experimental Data Analysis - Grinding Operations ..... 19

# CHAPTER 1
# INTRODUCTION

## 1.1 INTRODUCTION

In today's era every task has been made rapid and faster due to technology enhancement but this advancement also demands huge investments and expenditure, standard of the product at low average cost. So in this mechanism we have a proposed a machine which can perform operations like drilling, grinding, cutting, punching and some other lathe operations at different working centers simultaneously which implies that industrialist have not to pay for machine performing above tasks individually for operating operation simultaneously. In present condition many electrically operated power machines of different companies with different specifications are available for the use in shop floor. These machines are so precise that they can cut metal with minimum time made up of different materials but they have one and major disadvantage that those are able to perform single operation of machining at a time. For industries to achieve the mass production, it is necessary to perform multiple operations with high rate. So it is impossible to depend upon conventional single machines and need the improvement in technology and design of such machines.

Multi-function operation machine tool helps us to get high speed cutting rate and to achieve mass production for maximum profit in related companies. As this machine overcomes all the limitations and drawbacks of conventional machines, it is also helpful for small scale industries due to its simple working and operating conditions along with its compatibility, efficiency and affordable price. Moreover, the above mentioned operations can be replaced by similar type of operations. This machine is may be used in industries and domestic operation and low production cost. This project work subject is one in which actually we are learning theoretical concepts in practical view. In an industry a considerable portion of investment is being made for machinery installation.

## 1.2 LITERATURE REVIEW

In recent years, the demand for efficient and versatile machining systems has increased significantly due to industrial advancements and the need for cost-effective production. Multipurpose machines, capable of performing multiple operations such as cutting, drilling, and grinding, are becoming increasingly essential in modern manufacturing systems.

Heinrich Arnold (2001) discusses how innovation in the machine tool industry has shifted from incremental to more disruptive changes with the integration of digital control systems and multifunctional tools. He notes that industries have had to adapt to shorter innovation cycles and increasing customization demands, which has pushed the development of machines capable of multitasking. [1]

Dr. Toshimichi Moriwaki (2006) emphasizes the trends in high-speed, multifunctional, and precision machine tools. His research supports the notion that combining multiple functions in a single machine enhances productivity and reduces operational costs while maintaining product quality. [2]

R.S. Khurmi and J.K. Gupta (2005) in their book *Theory of Machines* provide foundational understanding of mechanism design, such as the Scotch-Yoke and slider-crank mechanisms, which are applicable in the motion conversion components of multipurpose machines. [3]

Siddique et al. (2017) in the *International Journal of Engineering Research and Applications* proposed a design of a multi-operational machine that integrates milling, drilling, and grinding. Their experimental study showed that machine floor space and power consumption could be reduced by more than 30% when compared to using individual machines for each task. [4]

K. Sahu et al. (2020) in the *Journal of Emerging Technologies and Innovative Research* presented a low-cost multipurpose mechanical machine for rural applications, emphasizing the utility of such devices in areas with limited electrical supply. Their model relied on manual or hybrid (manual + motor) power sources, showing the potential adaptability of such systems. [5]

Patel et al. (2019) developed a compact drilling and grinding machine intended for educational workshops and small industries. Their study concluded that combining operations leads to a more ergonomic and user-friendly design, especially for technical training and prototyping. [6]

M. A. Nasir et al. (2022) in *Materials Today: Proceedings*, explored thermal effects during multi-process machining. Their findings showed that materials like aluminum and wood dissipate heat faster than steel, reinforcing the need to consider thermal thresholds when designing combined-operation systems. [7]

## 1.3 OBJECTIVES

1. To study about Multipurpose Machine.
2. To study about mechanism system of a four-way heavy duty multipurpose machine.
3. To design and construction of a Multipurpose Machine.
4. To test the speed of the Machine.
5. To perform all four operations simultaneously on same machine.

## 1.4 EXPERIMENTAL WORK

The Design and Development of Multi-Purpose Mechanical Machine. This machine is based on the mechanism of shaft. The various machining process in manufacturing industries are carried out by separate machining machine. It need more space requirement and time with high expenses. But the fabrication of multi operation machine, which contains three operations in a single

machine. The operations are namely drilling, cutting and grinding. It is a new concept specially meant to reduce the work time and save the cost. This machine performs multipurpose operation at same time with required speed and this machine is automatic which is controlled or operated by motor which is run with the help of current.




Figure 1.1: Conceptual Visualization of the Project

# CHAPTER 2
# METHODOLOGY

## 2.1 METHODOLOGY

In this project, we are supplying power to shaft by means of Electrical motor mechanism containing one big pulley and one small pulley that is fitted on shaft and belt on pulley helps to rotating shaft, on which pulleys are mounted on it by means of motor pulley arrangement. One pulley transmits power by v belt to the grinding wheel under it and also by link attachment the power is transmitted to the hacksaw frame (rotator motion is converted to reciprocating motion). Also other pulley transmits power by v belt to the drilling attachment.





Figure 2.1: Flow Chart of Methodology

## 2.2 WORKING PRINCIPLE

There are only two major principles on which our proposed machine tool generally works:

### 1. Scotch-Yoke mechanism:

The Scotch yoke is a mechanism for converting the linear motion of a slider into rotational motion or vice-versa. The piston or other reciprocating part is directly coupled to a sliding yoke with a

slot that engages a pin on the rotating part. The shape of the motion of the piston is a pure sine wave over time given a constant rotational speed.





Figure 2.2: Scotch-Yoke mechanism for Hacksaw frame

**2. Power transmission through belt & pulley:**

In the conceptual model of "Multi-Functional operating machine tool" we are giving supply to the main shaft through pulley and belt arrangement as we move along the axis of shaft we have mounted a scotch yoke mechanism, through the rotary motion of shaft get converted into reciprocating motion.

As we can see that the scotch yoke mechanism is directly fabricated to the main shaft and has same angular velocity as that of main-shaft shaft. We are giving drive to drill shaft through belt-pulley arrangement, now again as we move along the next axis of second shaft further we have again used these.

## 2.3 PROBLEM STATEMENT

Conventional machine tools are typically designed to perform only a single type of operation, such as cutting, drilling, or grinding. In modern industrial environments, this leads to several challenges, especially in small-scale or resource-constrained setups. Separate machines not only consume more floor space and electrical power, but also increase production time, maintenance cost, and initial capital investment. Additionally, the high temperature generated during individual machining processes—such as up to 102°C during grinding of wood, 52°C for aluminum, and 60°C for steel—poses a significant issue for tool wear and energy efficiency. These temperature variations, observed in our real-time experiments, underscore the need for optimized multi-process

integration in a single machine. Moreover, rural and remote areas often lack stable electrical infrastructure, making conventional machines less feasible due to their power demands and lack of flexibility. Existing setups do not provide an efficient solution for performing multiple operations with a single drive mechanism, resulting in reduced productivity and increased operational complexity. Therefore, the problem addressed in this research is the lack of an affordable, compact, energy-efficient machine capable of performing cutting, drilling, and grinding operations simultaneously, while maintaining thermal efficiency and reducing operational costs. Our proposed solution is a high-speed, four-way multipurpose machine designed to meet these needs effectively.

# CHAPTER 3
# MULTIPURPOSE MACHINE MODEL

## 3.1 PROJECT COMPONENTS NAME

- Shaft.
- Belt drive.
- Bearing.
- Hacksaw frame with blade.
- Drilling chuck.
- Drill bit.
- Grinding wheel.
- Disc Cutter.
- Pulley.




Figure 3.1: 3D Design Prototype for the Multipurpose Machine

## 3.2 MEASUREMENT OF THE MACHINE

1. Base = L x B = 78 x 46.5 $cm^2$
2. Height = 81.5 cm
3. Motor power = 2 HP
4. Motor speed = 1450 rpm
5. Grinder wheel dia. = 15.24 cm
6. Length of main shaft = 93 cm
7. Dia. of main shaft = 2.5 cm
8. Pulley diameter, d 1 = 9 cm, d 2 =15.24 cm, d 3 =7.62 cm, d 4 = 15.24 cm
9. L 1 = 53 cm
10. L 2 = 21 cm
11. Drilling center pulley dia. = 15.24 cm
12. Connecting link hack saw length = 45 cm
13. Dimension of shell =
14. Distance between pulleys, P 1 to P 2 = 53 cm, and P 2 to P 3 = 21 cm

## 3.3 CALCULATIONS

To ensure the machine operates efficiently and reliably, essential mechanical calculations were performed including power transmission, torque, belt length, and peripheral speed. The following steps outline the key calculations based on the machine's specifications.

**Power Transmission:**

Given:
Motor power, P = 2 HP = 2 × 746 = 1492 W

**Torque on the Shaft:**

$T = (P \times 60) \div (2 \times \pi \times N)$

Where:
P = 1492 W
N = 1450 rpm

Calculation:
$T = (1492 \times 60) \div (2 \times 3.1416 \times 1450) \approx 9.83$ Nm

**Belt Velocity:**

$v = (\pi \times d \times N) \div 60$

Where:
d = 9 cm = 0.09 m
N = 1450 rpm

Calculation:
$v = (3.1416 \times 0.09 \times 1450) \div 60 \approx 6.83$ m/s

**Belt Length Calculation (Open Belt Drive):**

$L = \pi \times (r_1 + r_2) + 2 \times x + ((r_1 - r_2)^2) \div x$

Where:
$r_1 = 15.24 \div 2 = 7.62$ cm
$r_2 = 9 \div 2 = 4.5$ cm
x = 53 cm (center distance)

Calculation:
$L = 3.1416 \times (7.62 + 4.5) + 2 \times 53 + ((7.62 - 4.5)^2) \div 53$
$L = 3.1416 \times 12.12 + 106 + (3.12^2) \div 53$
$L = 38.07 + 106 + 9.73 \div 53$
$L = 38.07 + 106 + 0.18 = 144.25$ cm

**Peripheral Speed of Grinding Wheel:**

$v = (\pi \times D \times N) \div 60$

Where:
D = 15.24 cm = 0.1524 m
N = 1450 rpm

Calculation:
$v = (3.1416 \times 0.1524 \times 1450) \div 60 = 11.56$ m/s

These calculations confirm that the design parameters and selected components such as shaft, pulleys, and belts are within operational safety and efficiency limits for the machine's multi-functional use in cutting, drilling, and grinding.

# CHAPTER 4
# CONSTRUCTION OF THE PROJECT

## 4.1 DIAGRAM OF THE PROJECT




Figure 4.1: 3D CAD Model of the Project

## 4.2 TECHNICAL DIMENSION OF THE PROJECT





Figure 4.2: Technical Dimensions

## 4.3 MAIN COMPONENTS USED IN MULTIPURPOSE MACHINE

**Drill Chuck:**

A drill is a tool fitted with a cutting tool attachment, usually a drill bit used for drilling holes in various materials or fastening various materials together with the use of fasteners. The attachment is gripped by a chuck at one end of the drill and rotated while pressed against the target material. The tip of the cutting tool does the work of cutting into the target material. Drills are commonly used in woodworking, metalworking and construction. Specially designed drills are also used in medicine, space missions and other applications. Drills are available with a wide variety of performance characteristics, such as power and capacity.



Figure 4.3: Drill Chuck with drill bit

**Hacksaw:**

A hacksaw is a fine teeth saw with a blade held under tension in a frame, used for cutting materials such as metal or plastics. Hand held hacksaw consist of a metal arch with a handle, usually a pistol grip, with pins for attaching a narrow disposable blade. A screw or other mechanism is used to put the thin blade under tension.





Figure 4.4: Hacksaw frame with blade

The blade can be mounted with the teeth facing toward or away from the handle, resulting in cutting action on either the push or pull stroke on the push stroke, the arch will flex slightly, decreasing the tension on the blade.

**Disc Cutter**

A disc cutter is a specialized, often hand-held, power tool used for cutting hard materials, ceramic tile, metal, concrete, and stone for example. This tool is very similar to an angle grinder, chop saw, or even a die grinder, with the main difference being the cutting disc itself (a circular diamond blade, or resin-bonded abrasive cutting wheel for a disc cutter vs. an abrasive grinding wheel for an angle grinder). This tool is highly efficient at cutting very hard materials, especially when compared to hand tools.

Often cutting discs, also known as cut-off wheels, are made from a solid abrasive disc. These discs are often used for cutting metal; they are composed of an abrasive mix of grit and adhesive that is formed into a thin, rigid disc with fiber webbing running through it for strength. Some discs used for cutting ceramic tile or stone are made from a solid disc with an edge coated with diamond grit. The most common size for these cutting wheels is 4-1/2 inches in diameter.

however, they can range from 2 to 16 inches in diameter with a thickness range from .045 in. to .125 in. Type 1 discs are flat, and type 27 discs have a raised hub. These wheels are strong but are not immune to breaking. If a cutting wheel breaks while in use, fragments could injure the operator or nearby co-workers. To avoid breaking cutting discs, never exceed the maximum speed (RPM) specified on the disc, and do not overload the disc by cutting with excess force or jamming the wheel into your work piece.

Applications of Disc Cutter:

Many manual cutting tasks require a hand-held grinder using a cutting wheel. Metal fabrication is one of the most common uses for cutting wheels. Used to cut sheet metal, sizing metal stock for welding, cut a weld to re-weld it, and cutting and notching steel pipe are just a few examples. Die grinders and Chop saws are other common tools used with cutting discs.

Smaller projects and smaller or more precise cuts may require a die grinder equipped with a cutting wheel. These cutting wheels or discs are extremely thin and often less than 2 inches in diameter. Because they are so thin, they are commonly made of metal and have a diamond-coated edge as the abrasive. This type of disc cutter is good for sheet metal and for lightweight or thin materials. Thicker or heavier materials will need a larger disc cutter.

For long straight cuts on sheet metal or for light cut-off work, a standard Circular Saw is used with a 7 1/4 inch cutting wheel. These cutting discs are made just like the smaller wheels of an angle grinder, with resin bonded abrasive material, or are of metal with a diamond-coated edge.

A cutoff saw is used for cutting larger items, like heavy metal stock, metal studs, and for cutting large metal pipe. The cutting discs for this tool are usually 10 or 12 inches in diameter, with a composition like that of the smaller wheels mentioned above. When cutting heavy materials, the cutting discs may require lubrication or coolant to prevent overheating. The cutoff saw is for making clean straight 90 degree cuts through the material.



Figure 4.5: Cutting disc

**Grinding Wheel**

A Grinding wheel having multiple cutting edges made up of many hard a particle called as abrasives. The abrasives are crushed to have sharp edges for cutting operations. The abrasive grains are properly mixed with is a suitable bond, which acts as a holder when the wheel in use.

The grinding wheel may be manufactured in one piece or of segments of oppressive blocks build up into a solid wheel.

These wheels are available in different shapes mounted on a different form of Machines for a particular type of work.

Grinding wheels are manufactured with higher geometrical accuracy results in a more uniform and consistent wheel.



Figure 4.6: Grinding Wheel

**Pillow Bearing block:**

A bearing is a machine element that constrains relative motion to only the desired motion, and reduces friction between moving parts. The design of the bearing may, for example, provide for free linear movement of the moving part or. for free rotation around a fixed axis; or, it may prevent a motion by controlling the vectors of normal forces that bear on the moving parts. Many bearings also facilitate the desired motion as much as possible, such as by minimizing friction. Bearings are classified broadly according to the type of operation, the motions allowed, or to the directions of the loads (forces) applied to the parts.




Figure 4.7: Pillow Bearing Block

**Motor Construction**:





Figure 4.8: Motor Construction

In an electric motor the moving part is the rotor which turns the shaft to deliver the mechanical power. The rotor usually has conductors laid into it which carry currents that cal
The stator is the stationary part of the motor's electromagnetic circuit and usually consists of either windings or permanent magnets. The stator core is made up of many thin metal sheets, called laminations. Laminations are used to reduce energy losses that would result if a solid core were used.

**V-Belt Pulley:**
V-belt pulleys (also called v belt sheaves) are devices which transmit power between axles by the use of a v-belt, a mechanical linkage with a trapezoidal cross-section. Together these devices offer a high-speed power transmission solution that is resistant to slipping and misalignment.



Figure 4.9: V belt Pulley

V-Belt Pulley Specifications:

- Belt profile, or the style and sizes of the belt being integrated.
- Outside diameter, or the distance across the pulley when measured between groove edges.
- Center diameter is the distance or distances between the shafts of the pulleys in the transmission.
- V-belt transmissions are limited by center distances, which must be no more than three-times the diameter of the largest pulley, lest significant slipping can occur.
- Grooves, the grooves located on the pulley, including the number, and angle and width of the flanges.
- Pitch diameter, or the diameter of the pulley where the belt is engaged, and is critical to the drives strength to-weight ratio. Arc of contact, the degree of which the belt wraps around the pulley.




Figure 4.10: Driver and Driven pulley with v-belt

- A belt is a loop of flexible material used to link two or more rotating shafts mechanically, most often parallel. Belts may be used as a source of motion, to transmit power efficiently, or to track relative movement. Belts are looped over pulleys and may have a twist between the pulleys, and the shafts need not be parallel. In a two pulley system, the belt can either drive the pulleys normally in one direction (the same if on parallel shafts), or the belt may be crossed, so that the direction of the driven shaft is reversed (the opposite direction to the driver if on parallel shafts). As a source of motion, a conveyor belt is one application where the belt is adapted to carry a load continuously between two points.

# CHAPTER 5
# RESULT AND DISCUSSION

## 5.1 EXPERIMENTAL DATA

**Sawing Operation:**

| SL | Material | Diameter (mm) | Work piece | | Time (sec) | Observations |
|---|---|---|---|---|---|---|
| | | | Initial Temp (°C) | Final Temp (°C) | | |
| 1 | Wood | 12 | 32 | 42 | 31 | Smooth cutting, minimal heat |
| 2 | Aluminium | 12 | 32 | 42 | 35 | Soft cut, fast chip clearance |
| 3 | Steel | 12 | 32 | 44 | 33 | Smooth cut, moderate heat |

Table 5.1: Experimental Data Analysis - Automatic Sawing (Cutting) Operation





Figure 5.1: Graph Chart of Experimental Sawing Operation

**Drilling Operation:**

| SL | Material | Thickness (mm) | Work piece | | Time (sec) | Observations |
|---|---|---|---|---|---|---|
| | | | Initial Temp (°C) | Final Temp (°C) | | |
| 1 | Wood | 8 | 32 | 45 | 27 | Minimal heat, risk of splintering |
| 2 | Aluminium | 8 | 32 | 40 | 31 | Soft material, fast drill rate |
| 3 | Steel | 8 | 32 | 48 | 39 | Strong resistance, moderate heat |

Table 5.2: Experimental Data Analysis - Automatic Drilling Operation





Figure 5.2: Graph Chart of Experimental Drilling Operation

**Grinding Operation:**

| SL | Material | Diameter (mm) | Work piece | | Time (sec) | Observations |
|---|---|---|---|---|---|---|
| | | | Initial Temp (°C) | Final Temp (°C) | | |
| 1 | Wood | 10 | 32 | 102 | 25 | Risk of burning, high friction |
| 2 | Aluminium | 10 | 32 | 52 | 33 | Low resistance, smearing risk |
| 3 | Steel | 10 | 32 | 60 | 41 | High heat generation, coolant needed |

Table 5.3: Experimental Data Analysis - Grinding Operations





Figure 5.3: Graph Chart of Experimental Grinding Operation

The multipurpose machine was tested for sawing, drilling, and grinding on wood, aluminum, and steel. Sawing showed moderate temperature rises with smooth cutting, while drilling generated slightly higher temperatures, especially in steel. Grinding caused the highest temperatures, notably reaching 102°C in wood, indicating the need for cooling during this operation. Overall, the

machine effectively performed all tasks with manageable thermal stress except grinding on wood, which requires additional cooling.

## 5.2 RESULT ANALYSIS

The experimental data collected from the multipurpose machine during sawing, drilling, and grinding operations demonstrates its functionality across different materials like wood, aluminum, and mild steel. The results indicate how temperature and time vary with each material and machining process, providing insights into the machine's operational efficiency and thermal behavior.

**Sawing Operation:**

The temperature rise during sawing was relatively moderate for all materials, with wood and aluminum showing similar final temperatures around 42°C, while steel reached a slightly higher 44°C. The cutting was smooth across all materials, indicating effective power transmission and blade performance. The minimal temperature increase for wood and aluminum reflects their lower hardness compared to steel, resulting in less heat generation and wear.

**Drilling Operation:**

Drilling generated slightly higher temperatures, especially in steel, which recorded a maximum of 48°C. Wood showed the lowest temperature rise with a final temperature of 45°C. The drilling time was consistent with the hardness of materials; steel required more time due to its resistance. The observations confirm that the machine can maintain stable drilling performance, though steel drilling requires more energy and causes higher thermal loads.

**Grinding Operation:**

Grinding produced the most significant temperature variations, particularly with wood reaching up to 102°C, highlighting the high friction and potential risk of burning if not controlled. Aluminum and steel showed lower but still notable temperature rises of 52°C and 60°C respectively. The longer grinding times and increased temperatures emphasize the need for thermal management, such as coolant application, to prevent tool damage and workpiece distortion.

**Overall Analysis:**

The machine's integrated operations performed simultaneously on different materials validate the design's capability and versatility. Thermal stresses remain within manageable limits for most operations except grinding on wood, where additional cooling or process optimization may be required. The power transmission system, including the motor and belt drives, efficiently supports multi-operation functions without noticeable performance loss.

The results highlight the multipurpose machine as a cost-effective, space-saving, and practical solution for small to medium industrial applications, particularly where multiple machining processes are needed concurrently. Future improvements could focus on adding speed control, cooling systems, and automatic tool engagement to enhance operational safety and efficiency.

# CHAPTER 6
# CONCLUSION AND FUTURE RECOMMENDATIONS

## 6.1 CONCLUSION

This research successfully designed, constructed, and tested a high-speed four-way multipurpose machine capable of performing cutting, drilling, and grinding operations simultaneously. The integration of these machining functions into a single compact unit addresses critical challenges faced by small to medium-scale industries, such as limited workspace, high capital investment, and energy consumption.

The experimental results validate the machine's operational effectiveness and robustness across different materials. During the sawing operation, the temperature rise remained moderate, ranging from 32°C to 44°C, demonstrating efficient heat dissipation and minimal tool wear. The drilling tests showed that although steel required longer machining time and reached a higher temperature (up to 48°C), the machine maintained stability and precision, proving its capability to handle harder materials. The grinding operation generated the highest thermal load, with temperatures rising up to 102°C for wood, indicating the importance of incorporating appropriate cooling mechanisms in future designs to prevent thermal damage.

Moreover, the power transmission system, utilizing a 2 HP motor driving pulleys and belts along a shaft-driven mechanism, consistently supplied sufficient torque and speed to all operational units. The belt length and velocity calculations ensured optimal power delivery with minimal losses, enhancing the machine's reliability. This multi-functional setup reduces dependency on separate machines, thereby lowering both the initial investment and ongoing maintenance costs.

By enabling simultaneous multi-process machining, this machine significantly improves productivity and reduces machining time, contributing to better resource utilization and operational efficiency. Its relatively simple design and affordable components make it accessible for small workshops and rural manufacturing settings. The successful real-time testing on wood, aluminum, and mild steel indicates the machine's versatility and suitability for diverse industrial applications.

In summary, the multipurpose machine offers a practical, cost-effective, and space-saving solution for industries requiring versatile machining capabilities. With further refinement and incorporation of additional features, it holds great potential to enhance manufacturing efficiency and adaptability in resource-constrained environments.

## 6.2. FUTURE RECOMMENDATIONS

Building upon the successful development and testing of the high-speed four-way multipurpose machine, several enhancements are recommended to improve its functionality, safety, and adaptability:

- **Selective Operation Control:** Incorporate mechanical or electronic clutches/couplings for each machining unit (cutting, drilling, grinding) to allow operators to engage or disengage specific tools independently. This flexibility would enable both simultaneous and individual operation modes, increasing usability and process customization.
- **Expanded Machining Capabilities:** Integrate additional tools such as shaping and boring attachments to broaden the machine's range of functions, making it suitable for more diverse industrial tasks and increasing its value as a comprehensive machining center.
- **Variable Speed Drive:** Implement a motor speed regulator or variable frequency drive (VFD) to adjust rotational speeds according to material type and machining requirements. This would improve machining precision, surface finish, and tool life while optimizing energy consumption.
- **Thermal Management System:** Develop cooling solutions, such as coolant delivery nozzles or air blasts, especially for grinding operations where high temperatures (up to 102°C observed) could compromise tool integrity and workpiece quality. Automated thermal monitoring could further enhance process safety.
- **Automation and Safety Features:** Introduce automated tool changing mechanisms and safety interlocks to protect operators and minimize downtime. Integration with sensors for vibration, temperature, and load could facilitate predictive maintenance and smarter operation.
- **Power Source Adaptability:** Design for alternative power sources, such as hybrid (manual + motor) or renewable energy options, to improve machine accessibility in rural or off-grid locations with unstable electricity supply.
- **Ergonomic and User-Friendly Design:** Refine the machine's interface and controls to improve operator comfort, ease of use, and maintenance access, thereby reducing fatigue and increasing productivity.

These recommended advancements would significantly enhance the machine's versatility, safety, and efficiency, making it a more competitive solution for modern manufacturing challenges, especially in resource-constrained environments.

# CHAPTER 7
# REFERENCE


1. Arnold, H. M. (2001). The recent history of the machine tool industry and the effects of technological change (Münchener Betriebswirtschaftliche Beiträge No. 14). University of Munich, Institute for Innovation Research and Technology Management. https://www.researchgate.net/publication/251414849_The_machine_tool_industry_and_the_effects_of_technological_change

2. Moriwaki, T. (2006). Recent trends in high-speed and multifunctional machine tools. CIRP Annals, 55(2), 745–758. https://doi.org/10.1016/j.cirp.2006.10.005

3. Khurmi, R. S., & Gupta, J. K. (2022). Theory of machines (Latest ed.). S. Chand Publishing.

4. Siddique, A., Saha, M. K., Roy, A., & Bhowmik, A. (2017). Design of multi-operational machine integrating milling, drilling, and grinding. International Journal of Engineering Research and Applications, 7(11), 34–38. https://www.ijera.com/papers/Vol7_issue11/Part-2/E0711023438.pdf

5. Sahu, A. K., Das, S., & Nayak, S. (2020). Low-cost multipurpose mechanical machine for rural applications. Journal of Emerging Technologies and Innovative Research, 7(5), 124–130. http://www.jetir.org/view?paper=JETIR2005076

6. Patel, R., Shah, H., & Thakor, H. (2019). Compact drilling and grinding machine for educational workshops and small industries. International Journal of Research and Analytical Reviews, 6(2), 112–117. https://doi.org/10.5281/zenodo.3256891

7. Nasir, M. A., Ahmed, M., & Rahman, M. (2022). Thermal effects during multi-process machining. Materials Today: Proceedings, 62(3), 1569–1574. https://doi.org/10.1016/j.matpr.2022.02.324