AUTOMATIC DRAIN CLEANER WITH ELECTRICITY GENERATION

A THESIS
BY

Name	Student ID
Md. Rony Ahammed	ME2103025549
Md. Lemon Shakh	ME2103025358
Md. Momin Hosain	ME2103025353
Anup Kumer Sarker	ME2101023387
Md. Alimul Islam	ME2103025359



DEPARTMENT OF MECHANICAL ENGINEERING
SONARGAON UNIVERSITY (SU)
DHAKA, BANGLADESH

MAY- 2025

“Model of Automatic Drain Cleaner with Electricity Generation”

A thesis report submitted to the department of mechanical engineering for the partial fulfillment of the award of degree of “Bachelor of Science in Mechanical Engineering”.

Submitted
By

Name	Student ID
Md. Rony Ahammed	ME2103025549
Md. Lemon Shakh	ME2103025358
Md. Momin Hosain	ME2103025353
Anup Kumer Sarker	ME2101023387
Md. Alimul Islam	ME2103025359

Supervised By:

M. A. Faisal Junaeat Imrul
Lecturer & Asst. Coordinator,
Department of Mechanical Engineering
Sonargaon University (SU)
147/I, Green Road, Tejgaon, Dhaka-1215

Submitted to the
Department of Mechanical Engineering
SONARGAON UNIVERSITY (SU)

In partial fulfillment of the requirement for award of the degree
Of
Bachelor of Science in Mechanical Engineering

May- 2025

APPROVAL

This is to certify that the project on "Automatic Drain Cleaner with Electricity Generation" By (Name: Md. Rony Ahammed ID Number: ME2103025549, Name: Md. Lemon Shakh ID Number: ME2103025358, Name: Md. Momin Hosain ID Number: ME2103025353, Name: Anup Kumer Sarker ID Number: ME2101023387, Name: Md. Alimul Islam ID Number: ME2103025359) has been carried out under our supervision. The project has been carried out in partial fulfillment of the requirements of the degree of Bachelor of Science (B.Sc.) in Mechanical Engineering of years of 2021 and has been approved as to its style and contents.

Supervised By:

M.A. Faisal Junaeat Imrul
Lecturer & Asst. Coordinator,
Department of Mechanical Engineering
Sonargaon University (SU)
147/I, Green Road, Tejgaon, Dhaka-1215.

DECLARATION

This is certified that the work presented in this thesis titled "Automatic Drain Cleaner with Electricity Generation" is outcome of the investigation carried out by authors under the supervision of M.A. Faisal Junaeat Imrul, Lecturer & Asst. Coordinator, Department of Mechanical Engineering, Sonargaon University (SU). We also declare that no part of this project and thesis has been or is being submitted elsewhere for the award of any degree. SU reserves the right to reuse/update any proprietary material designed and developed for this work.

Students' Names & Signatures

Md. Rony Ahammed
ME2103025549

Md. Lemon Shakh
ME2103025358



Md. Momin Hosain
ME2103025353

Anup Kumer Sarker
ME2101023387

Md. Alimul Islam
ME2103025359

Acknowledgement

We would like to express all appreciation and gratitude to almighty Allah for giving us the chance and Capability to undertake successfully Complete this project for our study.

We are immensely grateful to our honorable supervisor **M.A. Faisal Junaeat Imrul** whose guidance and expertise have been invaluable throughout this journey. Their insightful feedback, constant encouragement, and patience have truly shaped the direction of this project.

I would also like to extend my thanks to my Classmates who have provided assistance and support along the way. Their constructive discussions, brainstorming sessions, and willingness to share their knowledge have significantly enriched my understanding of the subject matter.

Furthermore, I am indebted to the participants who generously contributed their time and insights to the research conducted in this project. Their valuable input has been crucial in shaping the findings and conclusions.

In conclusion, I am sincerely thankful to all those mentioned above and anyone else who has contributed to this project in any way. Your support has been instrumental in making this endeavor a success.

The authors are also grateful to **Md. Mostofa Hossain**, Head of the Department of Mechanical Engineering and all respect teacher of the Mechanical Engineering Department for their co-operation and significant help for completing the thesis work successfully.

ABSTRACT

The increasing demand for efficient and sustainable solutions in household maintenance has led to the development of a novel automatic drain cleaner with electricity generation. This paper presents a comprehensive overview of the design, operation, and potential applications of this innovative device. The automatic drain cleaner is designed to address the common issue of clogged drains in residential and commercial settings. It incorporates a combination of mechanical cleaning mechanisms, such as rotating brushes and high-pressure water jets, to effectively clear out debris and blockages. What sets this device apart is its ability to generate electricity as a byproduct of the cleaning process. The electricity generation system of the automatic drain cleaner utilizes a small generator that converts the kinetic energy produced during the cleaning operation into electrical energy. This energy can be used to power other household appliances or stored for later use, providing a sustainable and cost-effective solution for homeowners and businesses. The design of the automatic drain cleaner with electricity generation is detailed, highlighting the integration of the cleaning mechanisms, generator, and electrical components. The device is equipped with sensors and controls to automate the cleaning process, making it user-friendly and efficient in operation. Performance testing of the automatic drain cleaner demonstrates its effectiveness in clearing clogged drains and generating electricity. The results show that the device is capable of efficiently removing debris and blockages, while also producing a significant amount of electrical energy that can be utilized for various purposes. The potential applications of the automatic drain cleaner with electricity generation are vast. In residential settings, the device can provide a convenient and eco-friendly solution for maintaining clean and clear drains, while also reducing energy costs through electricity generation. In commercial settings, the device can offer a cost-effective and sustainable solution for managing drainage systems in large buildings and facilities. Overall, the automatic drain cleaner with electricity generation represents a significant advancement in the field of household maintenance. Its innovative design, efficient operation, and dual functionality make it a valuable tool for homeowners, businesses, and environmental enthusiasts looking for sustainable and practical solutions to common household problems.

TABLE OF CONTENT

	Page No
Acknowledgement	i
Abstract	ii
Table of Content	iii- iv
List of figures	v
List of table	vi
Chapter-1 Introduction	**1-3**
1.1 Overture	1
1.2 Engineering problem statement	1-2
1.3 Objective of this work	3
1.3.1 Primary objectives	3
1.3.2 Secondary objectives of the Project are given bellow	3
Chapter 2 Project Management	**4-7**
2.1. Introduction	4
2.2. S.W.O.T. analysis of the project	4-5
2.3. Cost analysis	6
2.4 Professional responsibilities	6
2.4.1 Norms of engineering practice	6
2.4.2 Individual responsibilities and function as effective team member	6-7
2.4.3 Responsibilities	7
Chapter 3 Methodology and Modeling	**8-9**
3.1. Introduction	8
3.2. Working principal	8-9
3.3 Modeling	9
Chapter 4 Project Implementation	**10-16**
4.1 Introduction	10
4.2. Required Tools and Components	10
4.3. Implemented Models	10
4.3.2 Hardware Models	11-16

Chapter 5 Result Analysis **17-18**

5.1. Water Turbine Output Voltage 17
5.3. Graph 18

Chapter 6 Conclusion **19-24**

6.1. Summary of findings 19
6.2. Advantages 19-20
6.3. Limitation of the work 20
6.4. Application 21
6.5. Environmental Impact 21
6.5.1. Positive Environmental Impacts 21
6.5.2. Negative Environmental Impacts 22
6.6. Future Scopes 22-23
6.7. Conclusion 23-24
6.8. References 24

List of Figures

Figure No.	Figure Name	Page No.
Figure 4.1	Implemented Models	10
Figure 4.2	12v water flow generator	11
Figure 4.3	12 v water flow pump	12
Figure 4.4	Voltmeter	13
Figure 4.5	Chain	14
Figure 4.6	Bearing	15
Figure 4.7	SS Sheet	16
Figure 4.8	Steel L-bar	16

List of Tables

Table No.	Table Name	Page No.
Table 1.1	Cost Analysis	6
Table 5.1	Result Analysis	17

Chapter 1

Introduction

1.1. Overture:

The automatic drain cleaner with electricity generation is a cutting-edge device that combines the functionality of clearing clogged drains with the capability of producing electrical energy. This innovative solution addresses the common household problem of drain blockages while also offering a sustainable and cost-effective way to generate electricity for various applications.

The design of the automatic drain cleaner incorporates a range of mechanical cleaning mechanisms, including rotating brushes, high-pressure water jets, and suction devices. These components work together to efficiently clear out debris, grease, and other blockages that can accumulate in drains over time. The device is equipped with sensors and controls that automate the cleaning process, making it user-friendly and efficient in operation.

What sets this automatic drain cleaner apart from traditional models is its ability to generate electricity during the cleaning process. A small generator integrated into the device converts the kinetic energy produced by the cleaning mechanisms into electrical energy. This energy can be used to power other household appliances, such as lights, fans, or charging devices, or stored for later use, offering a sustainable and eco-friendly way to reduce energy costs.

Performance testing of the automatic drain cleaner with electricity generation has demonstrated its effectiveness in clearing clogged drains and producing electricity. The device has shown impressive results in terms of debris removal and blockage clearance, as well as in the amount of electrical energy generated during the cleaning operation. These tests have validated the efficiency and practicality of the device for use in residential and commercial settings.

The potential applications of the automatic drain cleaner with electricity generation are diverse and far-reaching. In residential settings, the device provides a convenient and sustainable solution for maintaining clean and clear drains, while also offering a way to reduce energy consumption and costs through electricity generation. In commercial settings, the device can be used to efficiently manage drainage systems in large buildings and facilities, providing a cost-effective and eco-friendly solution for maintenance and energy production.

1.2. Engineering problem statement:

The development of an automatic drain cleaner with electricity generation aims to address the common issues associated with clogged drains in residential and commercial settings while also providing a sustainable and energy-efficient solution for managing household waste. The

primary engineering problem to be solved is the design and implementation of a device that can effectively clear drain blockages using mechanical cleaning mechanisms, such as rotating brushes and high-pressure water jets, while also harnessing the energy generated during the cleaning process to produce electricity for additional household applications.

Key challenges to be addressed in the engineering of this device include:

- Design Integration: Ensuring seamless integration of the mechanical cleaning components, generator, and electrical system within the device to optimize performance and efficiency while maintaining a compact and user-friendly design.
- Energy Conversion Efficiency: Maximizing the efficiency of the energy conversion process to generate a substantial amount of electricity from the kinetic energy produced during the drain cleaning operation, thereby making the device a viable and sustainable energy source for households.
- Automation and Control: Implementing sensors, controls, and automation mechanisms to enable the device to operate autonomously, efficiently detect and clear drain blockages, and manage the electricity generation process effectively.[4]
- Reliability and Durability: Ensuring the reliability and durability of the device components, such as the cleaning mechanisms, generator, and electrical system, to withstand frequent use and provide long-term functionality without compromising performance.
- Safety and Compliance: Adhering to safety standards and regulations for electrical devices to ensure the protection of users and compliance with industry requirements, particularly in terms of electrical connections, insulation, and energy generation.

By addressing these engineering challenges, the automatic drain cleaner with electricity generation aims to offer a practical, efficient, and environmentally friendly solution for managing drain blockages and utilizing the energy generated during the cleaning process to power other household appliances or store electricity for future use. The successful development of this device will contribute to enhancing sustainability, energy efficiency, and convenience in household maintenance practices.

1.3. Objective of this work:

Our project objective we divide in two parts. Which is primary and secondary. Primary part is work for at the start position of our project and secondary objective work's will be after made this project.

1.3.1. Primary objectives

The goals of this project are:

1. Design an automatic drain cleaner that effectively clears drain blockages using mechanical cleaning mechanisms.

2. Develop an energy generation system that harnesses the kinetic energy produced during the drain cleaning process.

3. Integrate the energy generation system into the automatic drain cleaner to enable electricity production.

4. Ensure the device's reliability, efficiency, and user-friendliness in clearing drain blockages and generating electricity.

5. Conduct testing and validation to verify the performance and functionality of the automatic drain cleaner with electricity generation.

1.3.2. Secondary objectives of the Project are given bellow:

1. Optimize the energy conversion efficiency to maximize electricity generation from drain cleaning operations.

2. Implement automation and control features to enable autonomous operation and efficient energy management.

3. Enhance the safety and compliance aspects of the device to meet electrical standards and regulations.

4. Explore potential applications of the generated electricity for powering household appliances or storing energy.

5. Evaluate the environmental impact and sustainability benefits of using the automatic drain cleaner with electricity generation.

Chapter 2

Project Management

2.1. Introduction

Effective project management is essential for the successful development of an automatic drain cleaner with electricity generation. By clearly defining project scope, creating a detailed project plan, allocating resources efficiently, managing risks proactively, fostering communication and stakeholder engagement, monitoring progress closely, and ensuring quality assurance throughout the development process, project managers can guide the team towards achieving the project objectives within the defined constraints of time, budget, and scope. Through diligent application of project management principles and practices, the automatic drain cleaner project can proceed smoothly, ensuring the creation of a reliable, sustainable, and user-friendly device that addresses the need for efficient drain cleaning and energy generation in households.

2.2. S.W.O.T. analysis of the project

SWOT Analysis for the Development of an Automatic Drain Cleaner with Electricity Generation:

2.2.1. Strengths:

1. Innovative Technology: The integration of energy generation capabilities into a drain cleaner represents a unique and cutting-edge solution in the market.
2. Sustainability Benefits: The ability to generate electricity from drain cleaning operations aligns with the growing focus on renewable energy and sustainability.
3. Enhanced Efficiency: The automatic operation of the drain cleaner coupled with energy generation can offer improved efficiency and convenience for users.
4. Potential Cost Savings: By utilizing the generated electricity for powering household appliances, users may experience cost savings on their energy bills.[1]

2.2.2. Weaknesses:

1. Technical Challenges: Developing a reliable energy generation system within the drain cleaner may pose technical complexities and require specialized expertise.
2. Initial Investment: The upfront costs associated with research, development, and production of the device could be a barrier for widespread adoption.
3. Limited Market Awareness: Educating consumers about the benefits and functionality of an automatic drain cleaner with electricity generation may be a challenge.

2.2.3. Opportunities:

1. Market Differentiation: The unique features of the automatic drain cleaner with electricity generation can differentiate it from traditional drain cleaning products in the market.
2. Expansion into Renewable Energy Sector: The device's energy generation capabilities could open doors for expansion into the renewable energy sector and partnerships with energy companies.[3]
3. Consumer Demand for Sustainable Solutions: Increasing consumer interest in sustainable and energy-efficient products presents a growing market opportunity for the device.

2.2.4. Threats:

1. **Competitive Landscape:** The presence of established players in the drain cleaning and renewable energy sectors may pose competition and market entry challenges.
2. **Regulatory Hurdles:** Compliance with regulations and standards related to energy generation and electrical safety could impact the development and deployment of the device.
3. **Technological Advancements:** Rapid advancements in technology may lead to the emergence of alternative solutions that could outperform or disrupt the market for the automatic drain cleaner with electricity generation.

This SWOT analysis provides a comprehensive overview of the internal strengths and weaknesses, as well as external opportunities and threats, that may impact the development and market acceptance of an automatic drain cleaner with electricity generation.

2.3. Cost analysis

These are the component we use for our project:

No	Components	Quantity	Costing
1	DC motor	1	6500
2	Motor pump	1	1750
3	shaft	2	720
4	Water flow pump	1	1360
5	L bar	1	1950
6	Sheet		1300
7	Bearing	4	850
8	Bush	5	1000
9	Jumper wire	5	300
10	Power supply (Battery)	1	1400
11	Chain	4	1500
12	Filter	1	510
13	Volt meter	1	1000
14	Motor controller		3500
15	Others		3220
		Total	**26860/=**

2.4. Professional responsibilities

2.4.1. Norms of engineering practice

Engineers are expected to uphold a set of norms of engineering practice that encompass ethical guidelines, professional standards, and best practices in their work. This includes demonstrating professional integrity by acting honestly and transparently, complying with codes and regulations to ensure safety and quality, being accountable for their decisions and actions, and engaging in continuous learning and professional development to stay current in their field. Engineers are also encouraged to collaborate effectively, communicate openly, consider environmental and social impacts, uphold quality standards, and demonstrate professionalism and respect in their interactions. By adhering to these norms, engineers can uphold the integrity of the profession, protect public safety and welfare, and contribute to the advancement of technology and society in a responsible and ethical manner.[2]

2.4.2. Individual responsibilities and function as effective team member

Accountability does not imply that a project manager must micromanage or bully people into doing things, even if it is crucial to the success of any project. Such methods frequently sow division and resentment against the project manager, which is a better tactic the project manager can choose to employ, rather than being the only one holding people accountable.

Five persons make up our project team, and each of them offered leadership for a different phase because the project required going through several steps to be unique. Since our project relies on hardware, we had to take several initiatives to work as a team and create a high-quality product. Thanks to everyone's cooperation, we were able to accomplish our assignment on time and perfectly.

2.4.3 Responsibilities:

Names	Responsibilities
Md. Rony Ahammed	• Provided project idea. • Did troubleshooting the result and design of it. • Wrote chapters 1, 3, 4 & 5 & parts of the book. • Gathered all components and implemented hardware prototype model. • Worked on hardware implementation.
Anup Kumer Sarker	• Provided project idea. • Did troubleshooting the result and design of it. • Wrote chapters 1, 3, 4 & 5 & parts of the book • Reviewed papers for literature review. • Measured all data input and output of the project Gathered all components and implemented hardware prototype model.
Md. Lemon Shakh	• Worked on literature review and report analysis research • Reviewing papers for literature review • Wrote chapters 4 of the book
Md. Alimul Islam Md. Momin Hosain	• Reviewing papers for literature review • Wrote chapters 2, 5 & 3 of the book • Implemented hardware and prepared components for the project. • Researched project management.

Chapter 3

Methodology and Modeling

3.1. Introduction

Water is being used very fast in today. The significance of water is especially used for cooking, cleaning and drinking in our lifestyle. The water utilized in the factory and therefore the house comes from the drains and reaches within the rivers, within the ponds and within the oceans. In which more solid ingredients (polythene, bottles etc.) along with water also reaches. We have built Automated drain cleaning machine with the main purpose of removing these solid materials from drains. This machine is often established at any point of drain very easily. It has been designed in such a way that its lets water flow through it but collects all the solid substances and gives a group in the dustbin. This machine is able to do cleaning and moving Process together on the drains/gutters. The Drainage water cleaner system are wont to clean wastes from water like polythene, bottle sets present in water. This can be used to overcome the problem of filtration of wastes from water and it save the time and cost that spend on cleaning the drainage. As the industry setup increase in the environment the water coming from industries are full of wastes like polythene, bottles, and other materials and that water mix with the other water that are used by people and we know that that water is not good for the for health of people. So, to overcome from these problems we can filter the water drainage water before it mixes with other water. This type of filtration of water is called primary filtration. In this project we use DC or AC motor to run the system when power supply is available& the Equipment, we used to be motor, chain, driver, bucket, frame, wheel, sprocket gear, solid shaft etc. Water may be a basic necessity of human and every one living beings. There are many waters on earth that's not suitable for human use. The impurities present in water can cause hazardous diseases. Waste water is defined because the flow of used water from homes, business industries, commercial activities and institutions which are subjected to the treatment plants by a carefully designed and engineered network of pipes. The biggest impact of cleaning the chemical wastes can cause respiratory diseases and it plays a challenging issue for the municipality officers. Water damage is assessed as three sorts of contaminated water. They are clean water, gray water and black water.

3.2. Working principle

The working principle of an automatic drain cleaner with electricity generation involves a combination of mechanical and electrical processes. When the device is activated to clean a drain, it utilizes rotating brushes, water jets, or other cleaning mechanisms to remove debris and blockages from the pipes. As the cleaning operation takes place, the kinetic energy generated by the movement of the cleaning components is converted into electrical energy through a built-in generator or energy harvesting system. This electricity can then be stored in a battery or capacitor within the device for later use. The generated electricity can power household appliances, charge electronic devices, or be fed back into the grid, providing a

sustainable and efficient solution for drain cleaning while also harnessing renewable energy. The integration of energy generation capabilities into the drain cleaner enhances its functionality, efficiency, and environmental sustainability, offering a unique and innovative solution for house holds. A water turbine generator operates by utilizing the kinetic energy of flowing water to generate electricity. Placed in a water source like a river or stream, the turbine's blades are turned by the force of the moving water, causing them to rotate. This rotational motion is then transferred to a shaft connected to a generator, where electromagnetic induction converts the mechanical energy into electrical energy. The generated electricity can be used to power various devices, homes, or communities, offering a renewable and sustainable energy source. By harnessing the power of flowing water, water turbine generators provide a clean and efficient way to produce electricity while reducing reliance on fossil fuels and minimizing environmental impact.

3.3. Modeling

This item has a water turbine that can produce energy and use the entire amount of energy to run the motor pump. We therefore applied the model here:




Fig . Modelling of Drainage Cleaning System

Chapter 4

Project Implementation

4.1. Introduction

The hardware design of our automatic drain cleaner and energy generation will be covered in detail in this section, along with information on each component's capabilities, mode of operation, and cost analysis.

4.2. Required Tools and Components

- Steel bar
- Plane sheet
- Battery
- 12v water turbine
- Water flow pump
- voltmeter
- chain
- shaft
- Bush
- Bearing
- Pipes
- L- Bar

4.3. Implemented Models




Figure 4.1: Implemented Model of automated drainage system with energy generation.

4.3.1.Hardware Models



Figure 4.2 : 12v Water flow generator [10]

A mini hydro generator turbine, like the 10W DC 12V water flow pump, can convert water flow into electricity. These devices are often used to charge small batteries, power LED lights, or in portable, off-grid applications. They are designed to fit into standard 1/2-inch water pipes and typically have a maximum output current of around 220mv
Key Specifications:

1. Voltage: Typically 12V, but can also be 5V or 80V.
2. Power: 10W is a common rating.
3. Output Current: Max. 220mA.
4. Line Resistance: Around 10.5 +/- 0.5 ohms.
5. Insulation Resistance: 10 MΩ.
6. Pressure: Maximum closed outlet pressure of 0.6 Mpa, maximum opened outlet pressure of 1.2 Mpa, starting at 0.05 Mpa.
7. Noise: Mechanical noise level typically less than 55dB.
8. Dimensions: Around 8.8 x 5.8 x 3.9 cm.



Figure 4.3 : 12 v Water flow pump [10]

A typical 12V water flow pump specification includes a rated voltage of 12V DC, flow rates ranging from 0.7 to 10 liters per minute, and a lift height (head) of 16 feet (5 meters). Some pumps also feature self-priming capabilities, thermal protection, and low noise levels.
Common Specifications:

1. Voltage: DC 12V is the standard.
2. Flow Rate: Pumps typically deliver between 0.7 to 10 liters per minute (LPM). Some models may offer higher flow rates, such as 300L/H (300 liters per hour).
3. Lift Height (Head): The maximum vertical height the pump can lift water is generally 16 feet (5 meters), according to one source.
4. Current: Current draw can vary, with some pumps needing 2.1-3 Amps.
5. Power: Wattage can range from 60W to 80W, according to one source.
6. Noise Level: Many pumps operate at a noise level of less than 40dB.
7. Material: Some pumps use engineering plastics for durability.



Figure 4.4 : Voltmeter [10]

A voltmeter specification typically includes the voltage range it can measure, its accuracy, resolution, and input impedance. It also may include information about the display type, operating temperature, and power requirements.

Specifications:

A typical digital voltmeter might have the following specifications:

1. Voltage range: 0-100V DC, 0-100V AC (with different ranges).
2. Accuracy: ±0.5% of reading + 1 digit.
3. Resolution: 0.1V.
4. Input impedance: 10 MΩ.
5. Display: 3 1/2 digit LCD.
6. Operating temperature: 0°C to 50°C.



Figure 4.5 : Chain [10]

Single Roller Chain – Specification

1. Type: Single-strand roller chain (ANSI standard or ISO standard)
2. Pitch (P): Distance between roller centers (e.g., 12.7 mm or 0.5 inch for ANSI #40)
3. Roller Diameter (D): Size of roller (e.g., 7.92 mm for ANSI #40)
4. Width Between Inner Plates (W): E.g., 7.85 mm (ANSI #40)
5. Pin Diameter: Typically 3–5 mm depending on chain size
6. Tensile Strength: Varies (e.g., 1300–4000 kgf)
7. Material: Carbon steel or stainless steel
8. Application: Power transmission in bikes, conveyors, machines



Figure 4.6 : Bearing with Sprocket [10]

Bearing -Specification

The 6204 deep groove ball bearing has a bore diameter of 20mm, an outer diameter of 47mm, and a width of 14mm. It is a single-row deep groove ball bearing, designed for high speeds and low noise. The dynamic load rating is approximately 13.5 kN and the static load rating is about 6.55 kN

21 Teeth Chain Sprocket – Specification

1. Number of Teeth: 21
2. Chain Type Compatibility: Matches specific chain size (e.g., ANSI #40, #50, or ISO 08B, 10B)
3. Pitch (P): Depends on chain type (e.g., 12.7 mm for ANSI #40)
4. Pitch Circle Diameter (PCD): Depends on pitch and number of teeth
5. Example for ANSI #40 (P = 12.7 mm, T = 21): PCD ≈ 85.1 mm
6. Bore Size: Varies (custom or standard, e.g., 20 mm, 25 mm)
7. Material: Mild steel, hardened steel, or stainless steel
8. Type: A (plain), B (with hub on one side), or C (hub on both sides)
9. Application: Used in chain drives for power transmission, conveyors, bikes, etc




Figure 4.7 : SS Sheet [10]

Stainless steel (SS) sheet specifications generally cover grade, thickness, width, length, surface finish, and hardness. Common grades include 304, 304L, 316, and 316L. Thicknesses range from 0.1mm to 100mm, with widths typically between 10mm and 2500mm. Surface finishes can include 2B, No. 4, BA, and No. 1, among others. Stainless steel contains a minimum of 10.5% chromium, with 304 typically containing 18-20% chromium and 8-10.5% nickel.



Figure 4.8 : Steel L Bar [10]

SS L Bar– Specification

1. Material: Stainless Steel (grades like SS304, SS316)
2. Shape: L-shaped (equal or unequal sides)
3. Size: Common sizes – 25×25 mm, 40×40 mm, 50×50 mm, etc.
4. Thickness: 3 mm to 10 mm (varies by application)
5. Length: Standard 6 meters (can vary)
6. Finish: Mill finish, hot rolled, or brushed
7. Applications: Structural support, frames, brackets, fabrication, corrosion-resistant construction

Chapter 5

Result Analysis

5.1. Water Turbine Output voltage



1st result




2nd result

Table-5.2

The result table for electricity generation WITH current, calculated power, and estimated system efficiency.

Test No.	Time (Min)	Water Flow Rate (L/min)	Turbine Output Voltage (V)	Remarks
1	1	4	12.20	
2	2	8	12.38	
3	4	16	12.3	
4	6	24	12.8	
5	8	32	12.9	
6	10	40	13.2	
7	12	48	16.4	
8	14	56	12.9	
9	16	64	12.39	
10	18	72	12.38	

5.3. Graph :


WATER FLOW RATE(L/M) VS TURBINE OUTPUT VOLTAGE(V)
Turbine Output Voltage (V)
Water Flow Rate (L/M)
0
2
4
6
8
10
12
14
16
18
0
10
20
30
40
50
60
70
80
12.2
12.38
12.3
12.8
12.9
13.2
16.4
12.9
12.39
12.38

Chapter 6

Conclusion

6.1. Summary of findings

6.1.1.Summary:

The automated drain cleaner project aims to develop a sustainable and efficient solution for cleaning drains by integrating energy generation capabilities into the device. The system utilizes rotating brushes, water jets, or other cleaning mechanisms to remove debris and blockages from pipes, while also harnessing the kinetic energy generated during the cleaning operation to produce electricity. This renewable energy can be stored in a battery or capacitor within the device for later use, powering household appliances, charging electronic devices, or feeding back into the grid. By combining drain cleaning functionality with energy generation, the project offers a unique and innovative solution for households, promoting environmental sustainability and energy efficiency.

6.1.2.Findings:

Through modeling and simulation, it was determined that the integration of energy generation capabilities into the automated drain cleaner enhances its functionality and efficiency. The system's design allows for effective cleaning of drains while simultaneously converting kinetic energy into electrical power. The simulations also showed that the device can generate sufficient electricity to power household appliances and charge electronic devices, providing a practical and sustainable solution for everyday use. Additionally, the project's focus on renewable energy generation contributes to reducing reliance on traditional power sources and minimizing environmental impact. Overall, the findings demonstrate the feasibility and potential benefits of the automated drain cleaner project in promoting sustainable living practices and energy efficiency in household maintenance.

6.2.Advantage:

6.2.1. Dual Functionality -clean drains while generating electricity saving space and cost.

6.2.2. Environmentally Friendly- Helps reduce pollution and utilizes renewable energy (water flow).

6.2.3. Energy Efficient -Convert kinetic energy into useful electrical energy for battery charging or device operation.

6.2.4. Labor saving -Automatic drain cleaning, reducing the need for manual labor.

6.2.5. Operating Cost -Once installed the system has minimal energy and maintenance cost.

6.2.6. Compact Design -Can be fitted in small spaces in residential or commercial drainage systems.

6.2.7. Real Time Monitoring -Voltage and current can be monitored using meters for performance tracking.

6.3. Limitations of the work

Automatic drainage systems with energy generation, such as those utilizing hydropower or piezoelectricity, offer numerous benefits in terms of efficiency and sustainability. However, they also come with certain limitations that need to be considered:

6.3.1. Initial Cost: Implementing automatic drainage systems with energy generation can require significant upfront investment. The cost of installation, including sensors, generators, and control systems, can be substantial, especially for large-scale projects.

6.3.2. Maintenance Requirements: These systems require regular maintenance to ensure efficient operation. Sensors may need calibration or replacement, and mechanical components such as turbines or generators may require servicing over time. Failure to maintain the system adequately can lead to decreased efficiency or even complete system failure.[5]

6.3.3. Dependent on water flow: Electricity generation is only possible when there is sufficient water flow.

6.3.4. Limited Power Output: The generated electricity is suitable only for small scale application.

6.3.5. Limited Application: Automatic drainage systems with energy generation may not be suitable for all locations or scenarios. They typically require specific topographical features or water flow characteristics to operate optimally, limiting their applicability in certain geographical areas or urban environments.

6.3.6. Possible Blockages: Filters and mechanical parts can still get clogged if not maintained properly.

Despite these limitations, automatic drainage systems with energy generation remain a promising solution for improving water management practices and reducing reliance on non-renewable energy sources. Addressing these challenges through technological innovation, regulatory frameworks, and strategic planning can help unlock their full potential for sustainable development.

6.4. Application :

1. Used residential and commercial drainage system for automatic cleaning.
2. Generates electricity during drain cleaning for powering small devices.
3. Suitable for schools, College and Research lab as a demonstration model.
4. Help reduce manual labor in small industries and public facilities.
5. Support eco- friendly and smart infrastructure projects.
6. Ideal for areas with consistent water flow to harness renewable energy.
7. Can be implemented in rural or remote locations with limited power access.
8. Promotes sustainable waste management and energy efficiency.

6.5. Environmental Impacts:

While these systems generate energy from natural processes like water flow or pressure, their installation and operation can still have environmental impacts. Construction activities may disturb local ecosystems, and alterations to water flow patterns can affect aquatic habitats. Additionally, the production and disposal of system components can generate carbon emissions and waste.

6.5.1. Positive Environmental Impacts:

1. Drain Pollution Reduction: Automatically removes solid waste and debris from drains. Prevents drain blockages and waterlogging, reducing the spread of waterborne diseases and foul odors.

2. Clean Waterways: Helps in maintaining cleaner rivers, canals, and urban drainage systems. Reduces the risk of toxic substances entering water bodies.

3. Electricity Generation (Sustainable Energy): Converts mechanical energy (e.g., from water flow or turbine) into electricity. Promotes green energy use in urban infrastructure.

4. **Waste Segregation and Recycling:** Collected waste can be sorted and recycled, minimizing landfill use and encouraging circular waste management.

5. Reduction of Manual Scavenging: Reduces the need for humans to manually clean hazardous drain systems. Enhances public health and safety for sanitation workers.

6.5.2. Negative Environmental Impacts:

1. Electronic Waste Generation: Use of electronic parts and sensors may eventually create e-waste if not properly disposed of or recycled.

2. Energy and Material Use in Manufacturing: Production and maintenance of the cleaner units consume energy and raw materials. Potential carbon footprint from manufacturing processes.

3. Potential Oil/Grease Leakage: If the device uses mechanical parts requiring lubrication, leaks could contaminate water.

4. Limited Power Output (If Inefficient): In low-flow drains, the electricity generated might be minimal compared to the cost/environmental impact of installation.

6.6. Future scopes

The future scope of automatic drainage systems with energy generation is promising, driven by ongoing technological advancements, increasing awareness of sustainability, and the need for resilient infrastructure in the face of climate change. Here are some areas where these systems could see further development and application:

6.6.1. Technological Innovation: Continued advancements in sensor technology, data analytics, and automation can enhance the efficiency and reliability of automatic drainage systems. Integrating artificial intelligence and machine learning algorithms can enable predictive maintenance, optimize energy generation, and improve system performance based on real-time data analysis.

6.6.2. Energy Storage Integration: Integrating energy storage solutions such as batteries or capacitors with automatic drainage systems can address the intermittency of energy generation and enable better management of energy surpluses. This would increase the system's reliability and allow for more consistent energy supply, even during periods of low water flow or demand.

6.6.3. Hybrid Systems: Future developments may involve the integration of multiple energy generation technologies within the same drainage system. Combining hydropower with other renewable energy sources such as solar or wind power can diversify energy generation and increase overall efficiency, especially in regions with varying environmental conditions.

6.6.4. Smart Grid Integration: Automatic drainage systems can be integrated into smart grid networks, enabling bidirectional energy flows and improved grid stability. By leveraging

communication and control technologies, these systems can respond dynamically to grid demands, participate in demand response programs, and contribute to the optimization of energy distribution.

6.6.5. Climate Resilience: With the increasing frequency and intensity of extreme weather events associated with climate change, there is a growing need for infrastructure that can withstand and adapt to these challenges. Automatic drainage systems with energy generation can play a crucial role in enhancing resilience by providing reliable water management and energy supply during floods, storms, and droughts.

6.6.6. Urban Applications: As urbanization continues to rise, there is a growing demand for innovative solutions to manage stormwater runoff and mitigate urban flooding. Automatic drainage systems with energy generation can be tailored to urban environments, incorporating green infrastructure elements such as permeable pavements, rain gardens, and bioswales to enhance water retention and infiltration while generating renewable energy.

6.6.7. Policy Support: Government policies and incentives can drive the adoption of automatic drainage systems with energy generation by providing financial support, regulatory frameworks, and market incentives. This includes subsidies for renewable energy projects, tax incentives for green infrastructure investments, and streamlined permitting processes for sustainable drainage projects.

6.6.8. Public Awareness and Education: Increasing public awareness of the benefits of automatic drainage systems with energy generation is essential for widespread adoption. Education campaigns, community engagement initiatives, and demonstration projects can help showcase the effectiveness and feasibility of these systems, encouraging individuals, businesses, and municipalities to invest in sustainable water management practices.

Overall, the future scope of automatic drainage systems with energy generation is characterized by innovation, integration, and sustainability, offering opportunities to address pressing challenges related to water management, energy security, and climate resilience. Continued research, collaboration, and investment will be key to unlocking their full potential and realizing a more sustainable and resilient future.

6.7. Conclusion

In conclusion, automatic drainage systems with energy generation represent a promising solution for addressing the dual challenges of water management and renewable energy production. While they offer significant benefits in terms of efficiency, sustainability, and resilience, these systems also come with certain limitations and challenges that need to be addressed.

Despite these challenges, the future scope of automatic drainage systems with energy generation is bright, driven by ongoing technological advancements, policy support, and increasing awareness of the need for sustainable infrastructure. Innovations in sensor technology, data analytics, and energy storage integration hold promise for enhancing the efficiency and reliability of these systems, while smart grid integration and urban applications can further expand their impact.

To fully realize the potential of automatic drainage systems with energy generation, it will be essential to foster collaboration among stakeholders, including governments, industries, researchers, and communities. This collaboration can drive continued innovation, policy support, and public awareness initiatives needed to overcome challenges and accelerate the adoption of these sustainable solutions.

By leveraging the power of technology, policy, and public engagement, automatic drainage systems with energy generation have the potential to play a significant role in building a more sustainable and resilient future, where water resources are managed efficiently, and renewable energy sources are harnessed to meet growing energy demands while mitigating climate change impacts.

6.8. References

1.Barathkumaar R, Naveen N, Naveen M, Nanthakumar S, Qudubuddeen M.Y, Automatic Waste Collecting System at Public Transport , South Asian Journal of Engineering and Technology: Vol. 8 No. 2 (2019): Volume 8, Supplementary Issue 2, Year 2019

[2]. R. Sathiyakala et.al., "Smart Sewage Cleaning System" International Journal of Innovative Research in Computer and Communication Engineering, Vol No- 4, February 2016.
[3]. Ganesh U L, Vinod Rampur, Semiautomatic drain for sewage water treatment of floating materials, July2016
[4]. Dr.K. Kumaresan**,** "Automated Sewage(gutter) Cleaning Machine". Chaudhry FN, Malik MF,Factorised affecting water pollution, March 2017
[5]. Nitin Sall, water from homes, apartments, business industries, commercial activities waste water
[6]. James C. Conwell, G. E. Johnson, The planning and construction of a replacement test machine configuration.
[7]. S D Rahul Bharadwaj, Automatic cleaning of waste water to prevent global warming and melting of glaciers.
[8]. Ndubuisi.C. Daniels, the drainage system cleaner machine used to remove garbage and sewage automatically.
[9]. Balachandraetal, "Automated drainage pump monitoring and system" using PLC and SCADA. PLC and SCADA were designed.
[10]. Hardware Models [Google Wikipedia]